

## Fanvil W710P DECT Phone System (W710P)



Product Name: Fanvil W710P DECT Phone System (W710P)

Manufacturer: Fanvil

Model Number: W710P

Fanvil W710P DECT Phone System (W710P)

The Fanvil W710P is a DECT IP system designed for small and medium-sized businesses.

Including the Base W710D and the handset W610D, it offers excellent mobility and flexibility, while eliminating the need for additional wiring costs. The system supports the registration of up to 10 Fanvil W610D DECT handsets and provides robust processing capacity for up to 20 SIP accounts and 10 simultaneous calls. Additionally, it supports LAN communication, allowing users to conduct internal calls without the need to register a SIP account. Fanvil IP DECT offers reliable wireless communication with high-quality voice service, perfect for dense user environments and short-range communication.

Fanvil W710P Key Features:

- 2.0" 240×320 colour screen
- Up to 10 handsets and 10 simultaneous calls
- Up to 20 SIP Server and 20 SIP Accounts
- Support outdoor range of up to 300 meters and indoor range of up to 50 meters
- 1 side key and 16 DSS keys
- Up to 8 hours' talk time and up to 160 hours standby time
- Support XML/LDAP Remote phone book
- Wireless signal coverage extends up to 50m indoors and 300m outdoors
- DECT technology for high-quality, reliable communication
- Supports firmware upgrades, configuration management, contactmanagement, and call record management operations on connected endpoints

Fanvil W710P Technical Specifications

General

• 10 simultaneous calls

• Wireless signal coverage: up to 50 meters indoors and 300 meters outdoors

• 10 terminals

• 20 SIP accounts

• 10 internal extensions

• 10 SIP Servers

• Supports multiple languages:

English/Japanese/Korean/French/German/Dutch/Spanish/Italian/Polish/Portuguese/Greek/Turkish/Russian/Chinese/Tra-Chinese

• 2.0-inch 240×320 color high-definition LCD display

• Support 16 virtual DSS Keys and 1 physical side key

• HD Voice

• Incoming vibration alarm

• Auto-Answering/Speed Dial /Call waiting/ 6-way Conference

Terminal Management

• Add/Delete/Import/Export

• Check terminal information

• Configure terminal: Reset, upgrade, DND

• Configuration management: 10 terminal configuration files

• Trouble removal: Capture package, syslog

## Fanvil W710P DECT Phone System (W710P)

- Local phone book: 1000 local contact for each terminal
- XML
- LDAP phone book
- 20000 call logs
- Call log statistics: All, Incoming, Outgoing, Missed, Forwards

### DECT

- Frequency band:

- 1880~1900 MHz (European/South Africa ):10 Channels
- 1920~1930 MHz (America ):5 Channels
- 1893~1906 MHz (Japan ):5 Channels
- 1880~1895 MHz (Taiwan,China ):8 Channels
- 1910~1920 MHz (Brazil ):5 Channels
- 1786~1792 MHz (South Korea ):3 Channels
- 1910~1930 MHz (Latin America ):10 Channels
- 1909~1929 MHz (Argentina ):10 Channels

### Network

- DECT protocol
- 10/100 Mbps Ethernet (Bridge connection)
- IP mode: IPv4/IPv6/IPv4&IPv6
- Static IP / DHCP
- 802.1x Network access permission authentication
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- CDP

### Audio

- Narrowband Codec: G.711a/u, G.729, G.729A, G.729B, G.729AB
- Wideband Codec: G.722, Opus

### Protocols

- DECT
- UDP/TCP/TLS
- RTP/SRTP
- STUN
- DHCP
- IPv6
- LLDP
- 802.1x
- L2TP
- openVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

## Fanvil W710P DECT Phone System (W710P)

For full specs see datasheet linked above  
limited-time-icon.jpg

**Price: £127.20**

---