



Product Name: Grandstream GWN7670LR Long-Range Dual-Band Wi-Fi 7 Access Point/Bridge (GWN7670LR)

Manufacturer: Grandstream Model Number: GWN7670LR

Grandstream GWN7670LR Long-Range Dual-Band Wi-Fi 7 Access Point/Bridge (GWN7670LR) The GWN7670LR is a long-range Wi-Fi 7 access point, ideal for medium-to-large businesses that need to provide long-range coverage. It offers IP66-level weatherproof capability, dual-band 2x2:2 MIMO with DL/UL OFDMA technology and a sophisticated antenna design for maximum network throughput and expanded Wi-Fi coverage range. It supports flexible switching between internal directional antennas and external omnidirectional antennas. It can be combined with directional antenna and PTMP technology (pending) to serve as a professional long-range wireless bridge. With 4096 QAM modulation, Wi-Fi 7 achieves a significant increase in data transfer rates. MLO technology optimizes spectrum resource utilization to ensure a smooth experience for every user. To ensure easy installation and management, the GWN7670LR uses a controller-less distributed network management design in which the controller is embedded within the product's Web User Interface.

The GWN7670LR is also supported by GDMS Networking and GWN Manager, Grandstream's cloud and on-premise Wi-Fi management platform. It is the ideal Wi-Fi AP for voice-over-Wi-Fi deployments and offers a seamless connection with Grandstream's Wi-Fi capable IP phones. With support for advanced QoS, low-latency real- time applications, mesh networks, captive portals, BLE 5.3, 256 concurrent clients per AP, 1x2.5 Gigabit network port with PoE+ and 1x 2.5 Gigabit SFP port. GWN7670LR is an ideal long-range Wi-Fi access point for enterprises, multiple floor offices, warehouses, parks, hospitals, schools and more. Grandstream GWN7670LR Key Features

آذِيًّ 3.6Gbps aggregate wireless throughput, 2.5Gbps aggregate wired throughput

� Integrated Wi-Fi 7 & Dystimes;2:2 MIMO with MLO, 4KQAM, MRU, Preamble Puncturing Technology

ï¿1/2 Up to 350-meter coverage range

� Supports 256 concurrent Wi-Fi client devices

آذِاً Advanced QoS to ensure real-time performance of low-latency applications

� Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device

ï¿⅓ Self-power adaptation upon auto-detection of PoE+

آذِاً Embedded controller manages up to 50 local GWN APs; GDMS Networking offers unlimited AP management, & AP management, & Manager offers on-premise software AP management

This access point is the first Grandstream access point to include a PTMP Bridge. Grandstream GWN7670LR Technical Specification Hardware Specifications
Radio

تز½ Antenna:

าะ// 2.4G: Directional internal 8dBi/External omni 3.5dBi เว่/2 5G: Directional internal 13.5dBi/External omni 3.5dBi

ï¿⅓ BT: 5.0dBi

Directional internal antenna beamwidth

� 2.4G: 90 degree � 5G: 35 degree



� MIMO: 2.4GHz: 2x2:2, MIMO, 5GHz: 2x2:2, MIMO

าั¿½ Frequency Bands: 2.4GHz Radio: 2400 - 2483.5 MHz, 5GHz Radio: 5150 - 5895 MHz \*Not all frequency bands can be used in all regions

าั¿½ Channel Bandwidth: 2.4G: 20 and 40 MHz, 5G: 20, 40, 80 and 160 MHz

آزٰ Wi-Fi Data Rates:

� 2.4G

IEEE 802.11be: Up to 688 Mbps IEEE 802.11ax: 7.3Mbps to 574 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

5G ½;ï

IEEE 802.11be: Up to 2882 Mbps IEEE 802.11ax: 7.3 Mbps to 2402 Mbps IEEE 802.11ac: 6.5 Mbps to 1732 Mbps IEEE 802.11n: 6.5 Mbps to 600 Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

\*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network

� Maximum TX Power: 2.4G: 27 dBm, 5G: 26 dBm \*Maximum power varies by country, frequency band and MCS rate � Receiver Sensitivity:

7.4G ½ 2.4G

802.11b: -96dBm @1Mbps, -88dBm @11Mbps; 802.11g: -93dBm @6Mbps, -75dBm @54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz: -70dBm @MCS7; 802.11ax 20MHz: -60dBm @MCS11; 802.11ax 40MHz: -58dBm @MCS11; 802.11be 20MHz: -65dBm @MCS11; 802.11be 40MHz: -62dBm @MCS11;

7¿½ 5G

802.11a: -92dBm @6Mbps, -74dBm @54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz: -70dBm @MCS7; 802.11ac 20MHz: -67dBm @MCS8; 802.11ac 40MHz: -63dBm @MCS9; 802.11ac 80MHz: -59dBm @MCS9; 802.11ax 20MHz: -60dBm @MCS11; 802.11ax 40MHz: -58dBm @MCS11; 802.11ax 80MHz: -56dBm @MCS11; 802.11ax 160MHz: -52dBm@MCS11; 802.11be 20MHz: -59dBm @MCS13; 802.11be 40MHz: -56dBm @MCS13; 802.11be 80MHz: -54dBm @MCS13; 802.11be 160MHz: -52dBm @MCS13;

ī¿½ Coverage Range: Up to 350 meters \*Coverage range can vary based on environment

12.1/2 Point to Multipoint (pending): 1 to 3 Up to 1.5 kilometers

تزر Bluetooth®: BLE 5.3

Interfaces



፲¿½ Network Ports: 1x 2.5G Ethernet WAN/LAN, RJ-45, PoE input, 1x 2.5G SFP

تزير LEDs: 1x tri-color LED for device tracking and status indication, 4x blue LED for signal

strength indication (PtMP mode)
12/2 Auxiliary Ports: 1x Reset Pinhole

#### Power

� PoE Input: 802.3at

ï¿1/2 Maximum Power Consumption: 15.5W

#### Physical

าั¿½ Dimension: Unit: 223.2 x 169.9 x 53.9 mm, Entire Package: 376 × 321 × 138 mm

آذِ1/2 Weight: Unit: 1.2k, Entire Package: 2.7kg

تزار Mounting: Wall mount or pole mount, kits included

าั¿½ Package Content: GWN7670LR Wi-Fi 7 Wireless AP, Mounting Kits, Quick Start Guide

#### Environmental

� Temperature: Operation: -30°C to 60°C, Storage: -40°C to 70°C

� Humidity: 10% to 90% Non-condensing

### Compliance

� Compliance

# Software Specifications WLAN

� Wi-Fi Standards: IEEE 802.11a/b/g/n/ac/ax/be

آزا SSIDs: 32 SSIDs total, 16 per radio (2.4GHz & mp; 5GHz)

ï¿1/2 Concurrent Clients: 256

ï¿⅓ Basics:

Beamforming OFDMA Multi-RU Preamble puncturing 4096-QAM Multilink operation (MLO) Target wake time (TWT) Maximal Ratio Combining (MRC) Space-Time Block Coding (STBC) Low-density Parity-Check (LDPC) 802.11 Dynamic Frequency Selection (DFS) BSS coloring

าั¿½ SSID Hidden: Restrict access and improve wireless network security by SSID hiding

፲¿½ Port Aggregation: Multiple uplink ports for port aggregation to increase uplink bandwidth

าั¿½ Multicast/Broadcast Suppression: Multicast/Broadcast enable optimization with ARP proxy

រី¿½ Multicast Enhancement: Convert multicast data into unicast data for transmission

『¿½ Bandwidth Limiting: Support SSID/Client/MAC/IP-based rate limiting

ī¿½ Band Steering/Client Steering: Guide client to the frequency band with more abundant spectrum resources

าั¿1/2 RRM: Dynamically assign radio power, channel

� VPN: L2TPv3

� VLAN: Support interface/SSID/MAC binding VLAN based, Management VLAN, Dynamic VLAN

ī¿½ Time Policy: Track the time that the client connects to Wi-Fi, Support setting the amount of time for the client to connect to Wi-Fi and the reconnec type after a timeout



ï¿1/2 Schedule: Supports SSID, LED, Reboot schedule

#### WLAN Extension

ï¿⅓ Bridge: Supported

ï¿1/2 Mesh: 2.4G, 2.4G & amp; 5G, 5G

ï¿1/2 Hotspot2.0: Supported

าั¿½ Wireless Roaming: 802.11k, 802.11v, 802.11r, Layer 2 roaming

#### Network

าั¿½ IPv4: Static or DHCP าั¿½ IPv6: Static or DHCP

� DHCP: Support server/client/relay

آزٰ½ NAT: NAT Pool

า๊¿½ LLDP: Link Layer Discovery Protocol, discovering and identifying other LLDP enabled devices and neighboring devices in the network

#### **User Authentication**

� 802.1x authentication: Supported

រី¿½ MAC authentication: Use client MAC address as the username and password for access control through the RADIUS server

ï¿1/2 PPSK: PPSK with/without RADIUS

� Captive Portal: Support radius/social login/vouchers/password/SAML SSO/active directory authentication

### Security

### � Encryption:

Open system OSEN WPA2-PSK (personal) WPA2-802.1x (enterprise) WPA3-SAE (personal) WPA3-802.1x (enterprise) WPA/WPA2, WPA2/WPA3 Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate and random default password per device

ī స్ట్రీ Forwarding Security: MAC filtering, Client isolation, OS filtering

าั¿½ WIDS: Inbound/outbound traffic rules, Rogue AP detection and containment, ARP attack defense, ND attack defense

### Service Quality

� QoS: 802.11e/WMM,802.1p, 802.1q, TOS

### Management Platform

آذِر Local Web: Embedded controller can manage up to 50 local GWN APs

ī¿1/2 GDMS Networking: A free cloud management platform for unlimited GWN APs

าั¿½ GWN Manager: premise-based software controller for up to 3,000 GWN APs

เ

2/2 GWN APP: Integrate GDMS Networking and GWN Manager to manage GWN APs via the APP

ï¿⅓ Management Protocol: TR-069, SNMP



**Price: 143.43EUR**