

Fanvil H602W Hotel IP Phone (H602W)



Product Name: Fanvil H602W Hotel IP Phone (H602W)

Manufacturer: Fanvil

Model Number: H602W

Please Note: This phone supports DC power only and is shipped with a power adapter included.

Fanvil H602W Hotel IP Phone (H602W)

The Fanvil H602W is a practical screenless hotel IP phone with an elegant design. It features six programmable keys and supports the wideband Opus HD audio codec, with built-in dual-band 2.4G & 5G Wi-Fi and support for Wi-Fi 6, offering more stable wireless connectivity while significantly reducing network deployment costs for hotels. The H602W is suitable for flexible deployments in various scenarios such as hotels, shopping malls, hospitals and supermarkets, providing users with a convenient and efficient experience. Fanvil H602W Technical Specifications: General

- 2 SIP Lines
- HD Voice
- Built-in dual-band 2.4G & 5G Wi-Fi 6
- Handset / Hands-free
- Desktop Stand
- Intelligent DSS keys (speed dial key)

Phone Functions

- Programmable DSS keys
- Action URL / Active URI
- Built-in dual-band 2.4G & 5G Wi-Fi 6: 2.4G 802.11 b/g/n/ax; 5G 802.11 a/n/ac/ax
- Web dial
- Dial plan
- SIP Hotspot
- Distinctive ring
- Multicast
- Built-in Wi-Fi SSID
- Speed Dial / Answer
- Voice Message
- Hot Line

Audio

- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.726, G.729A/B, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Cancellor (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR) / Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band (RFC2833 / SIP INFO)
- VQM voice quality monitoring

Network

- Physical: 10/100 Mbps Ethernet

Fanvil H602W Hotel IP Phone (H602W)

- IP Mode: IPv4 / IPv6 / IPv4&IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Wi-Fi Encryption: WPA / WPA2-PSK / 802.X EAP
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN: 802.1P/Q
- LLDP
- QoS
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Protocols

- SIP v1 (RFC2543), v2 (RFC3261) over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPv6
- PPPoE
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

Deployment & Management

- Auto-provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web management portal
- Web-based packet dump
- Configuration export / import
- Firmware upgrade
- Syslog

Other Physical Features

- Keypad: 21 keys (12 standard phone digit keys, 6 DSS keys, 3 function keys: Up/Down/Hands-free)
- MSG indicator (red LED) x1
- RJ9 Port x1: Handset x1
- RJ45 Port x1: Network x1
- Power: DC 5V 1A
- Power Consumption (Adapter): 0.9W~1.7W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation: Desktop
- Color: Black
- Dimensions (W x D x H): 12.8 x 19.5 x 4.9 cm

Package Contents

- 1 x Fanvil H602W Hotel IP Phone
- 1 x Handset
- 1 x Handset Cord
- 1 x 1.5m CAT5 Ethernet Cable

Fanvil H602W Hotel IP Phone (H602W)

1 x Power Adapter

Price: Â£69.40
