

Fanvil W710D DECT IP Base Station (W710D)



Product Name: Fanvil W710D DECT IP Base Station (W710D)

Manufacturer: Fanvil

Model Number: W710D

Fanvil W710D DECT IP Base Station (W710D)

The Fanvil W710D is a DECT IP base station designed for small and medium-sized businesses. When paired with Fanvil DECT phones, it offers excellent mobility and flexibility, while eliminating the need for additional wiring costs. The system supports the registration of up to 10 Fanvil DECT phones and provides robust processing capacity for up to 20 SIP accounts and 10 simultaneous calls. It also supports LAN communication, allowing users to conduct internal calls without registering a SIP account. The W710D offers reliable wireless communication with high-quality voice service, perfect for dense user environments and short-range communication. Fanvil W710D

Technical Specifications:

Key Features

- Up to 10 simultaneous calls
- Up to 10 Handsets
- Up to 20 SIP accounts
- Up to 10 internal extensions
- Support XML / LDAP Remote phone book
- Local phone book: 1000 local contacts for each terminal
- Wireless signal coverage: up to 50m indoors and 300m outdoors
- 10 SIP Servers

Terminal Management

- Add / Delete / Import / Export, check terminal information
- Configure terminal: Reset, upgrade, DND
- Configuration management: 10 terminal configuration files
- Trouble removal: Capture package, syslog
- Local phone book: 1000 local contacts for each terminal, XML, LDAP phone book
- 20,000 call logs
- Call log statistics: All, Incoming, Outgoing, Missed, Forwards

Network

- DECT protocol
- 10/100 Mbps Ethernet (Bridge connection)
- IP mode: IPv4 / IPv6 / IPv4&IPv6
- Static IP / DHCP
- 802.1x Network access permission authentication
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- CDP

Deployment & Maintenance

- Auto-Provisioning via FTP / TFTP / HTTP / HTTPS / DHCP OPT66 / SIP PnP / TR-069
- Web management interface
- Web-based Packet-dump
- Configuration export/import
- Firmware upgrade
- Syslog

Fanvil W710D DECT IP Base Station (W710D)

• Supports multiple languages: English / Japanese / Korean / French / German / Dutch / Spanish / Italian / Polish / Portuguese / Greek / Turkish / Russian / Chinese / Tra-Chinese

Protocols

- DECT
- UDP / TCP / TLS
- RTP / SRTP
- STUN
- DHCP
- IPv6
- LLDP
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP / TFTP
- HTTP / HTTPS
- TR-069

Audio

- Narrowband Codec: G.711a/u, G.729, G.729A, G.729B, G.729AB
- Wideband Codec: G.722, Opus

DECT

- Frequency band: 1880~1900 MHz (European / South Africa): 10 Channels, default item
- 1920~1930 MHz (America): 5 Channels
- 1893~1906 MHz (Japan): 5 Channels
- 1880~1895 MHz (Taiwan, China): 8 Channels
- 1910~1920 MHz (Brazil): 5 Channels
- 1786~1792 MHz (South Korea): 3 Channels
- 1910~1930 MHz (Latin America): 10 Channels
- 1909~1929 MHz (Argentina): 10 Channels

Other Physical Features

- 1 Reset Key
- Shell Material: Plastic Shell
- DC Input: 5V/1A
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- Power: DC 5V/1A or PoE
- Power Consumption (PoE): 1.17W ~ 1.39W
- Power Consumption (Power Adapter): 0.803W ~ 0.94W
- Installation: Wall-mounted
- Working Temperature: -10°C ~ +45°C
- Storage Temperature: -20°C ~ +60°C
- Working Humidity: 5% to 95%
- Colour: Gunmetal
- Dimensions (W x D x H): 14.0 x 10.0 x 2.6 cm

Package Contents

- 1 x Fanvil W710D DECT IP Base Station

Fanvil W710D DECT IP Base Station (W710D)

Price: Â£92.80
