

Grandstream RFID Card for GDS Series (RFID-CARDBUNDLE)



Product Name: Grandstream RFID Card for GDS Series (RFID-CARDBUNDLE)

Manufacturer: Grandstream

Model Number: RFID-CARDBUNDLE

Please Note: This RFID Card is compatible with Grandstream GDS series IP door systems and the Grandstream USB RFID Card Reader. It is not compatible with other manufacturers' access control systems.

Grandstream RFID Card for GDS Series (RFID-CARDBUNDLE)

The Grandstream RFID Card is a 125KHz contactless proximity induction card designed for use with the Grandstream GDS series of IP Door Systems and the Grandstream USB RFID Card Reader. This non-writable passive card receives radio energy from the RFID Card Reader to power the card and enable interaction with any GDS series device. It is easy to set up and use, making it ideal for a wide range of facility access, attendance, and security applications. Grandstream RFID Card Specifications:

- Card type: ID Card (TK4100)
- Working frequency: 125KHz
- Storage capacity: 64 Bit Read-Only
- Operating distance: 2~15 cm
- Life span: >100,000 times
- Packaging materials: PVC, ABS
- Encapsulation method: PVC Laminated
- Power supply mode: Passive Card (no battery)
- Working temperature: -20°C to 55°C
- Storage temperature: -20°C to 80°C
- Dimensions: 85.5 x 54 x 0.93mm (±0.5mm)

Please Enquire