

Grandstream 2-Line Carrier Grade IP Phone (GRP2610P)



Product Name: Grandstream 2-Line Carrier Grade IP Phone (GRP2610P)

Manufacturer: Grandstream

Model Number: GRP2610P

Grandstream 2-Line Carrier Grade IP Phone (GRP2610P)

The Grandstream GRP2610P 2-Line Carrier-Grade IP Phone is engineered for high-volume deployments and professional communication environments. Supporting 2 SIP accounts and featuring a bright 2.4-inch colour LCD, it delivers clear, user-friendly navigation and efficient call handling.

Built with HD audio, Opus support, and Grandstream's Noise Shield technology, the GRP2610P ensures exceptional voice clarity on every call. Designed with centralised provisioning through Grandstream's Device Management System (GDMS), it offers streamlined configuration and management.

With integrated PoE, enterprise-grade security, and a swappable faceplate for custom branding, the GRP2610P is ideal for businesses, service providers, and call centres seeking a powerful and scalable VoIP solution.

Specifications

General Features:

•

SIP Accounts: Supports 2 SIP accounts and 2 multi-purpose line keys

•

Display: 2.4-inch (320x240) TFT colour LCD

•

Faceplate: Swappable faceplate for easy logo customization

•

Noise Shield Technology: Minimises background noise

•

Device Management: Supported by Grandstream's Device Management System (GDMS)

•

PoE Support: Integrated Power-over-Ethernet (802.3af)

Audio & Conferencing:

•

HD Audio: Supports wideband codecs including G.722 and Opus

•

Speakerphone: Full-duplex speakerphone

•

Audio Conferencing: Supports 5-way audio conferencing

Voice Codecs Supported:

Grandstream 2-Line Carrier Grade IP Phone (GRP2610P)

i₂¹/₂
G.711 µ/a-law

i₂¹/₂
G.722 (wideband)

i₂¹/₂
G.726

i₂¹/₂
G.729A/B

i₂¹/₂
G.723

i₂¹/₂
iLBC

i₂¹/₂
OPUS

Call Management Features:

i₂¹/₂
Call hold, transfer, forward, park, pickup

i₂¹/₂
Call waiting, call log (up to 1000 records)

i₂¹/₂
Off-hook auto dial, auto answer, click-to-dial

i₂¹/₂
Hot-desking, personalized ringtones, and music on hold

i₂¹/₂
Server redundancy and failover support

Security & Provisioning:

i₂¹/₂
Security: Secure boot, dual firmware images, encrypted data storage

i₂¹/₂
Provisioning: GDMS, TR-069, AES-encrypted XML configuration files

i₂¹/₂
Authentication: MD5 and MD5-sess based authentication

Power & Energy Efficiency:

Grandstream 2-Line Carrier Grade IP Phone (GRP2610P)

⌘½

Power Supply: Universal 100-240VAC input; Output +5VDC, 600mA

⌘½

PoE Support: IEEE802.3af Class 1 (3.84W)

⌘½

Energy Efficiency: IEEE802.3az (EEE)

Environmental & Physical:

⌘½

Operating Temperature: 0°C to 40°C

⌘½

Storage Temperature: -10°C to 60°C

⌘½

Humidity: 10% to 90% non-condensing

⌘½

Dimensions: 208mm (L) x 180mm (W) x 63.4mm (H)

Compliance:

⌘½

Certifications: CE, FCC Part 15 Class B, RCM, ICES-003v

Price: Â£46.30
