

2N IP Force 2.0 IP Video Intercom 1 Button with Camera (9151301C)



Product Name: 2N IP Force 2.0 IP Video Intercom 1 Button with Camera (9151301C)

Manufacturer: 2N Telecommunications

Model Number: 9151301C

2N IP Force 2.0 IP Video Intercom 1 Button with Camera (9151301C)

The 2N IP Force 2.0 (9151301C) is the world's most durable IP video intercom, designed for demanding environments where maximum security, seamless access control, and precise visitor identification are essential. It features a 5MPx wide-angle camera with WDR and adaptive face zooming, ensuring clear colour images even in low light and switching to infrared night vision only in complete darkness. The robust aluminium (ADC12) body carries an IP69 and IK10 rating, with a protective dome over the camera lens for added shatter resistance. The 9151301C delivers clear, reliable audio with noise cancellation, a 10W high-volume speaker, adaptive volume control, and automatic audio-loop testing. It supports SIP 2.0, H.264/H.265 video, ONVIF, and QR code access powered by the Axis ARTPEC-8 processor, with secure boot, signed firmware, and a secure key store. Power is supplied via PoE+ (IEEE 802.3at) and management is via web GUI, My2N cloud, or third-party access control integration via OSDP. 2N IP Force 2.0 (9151301C)

Technical Specifications:

Power Supply

⚡ Type: 12V / 4A DC or PoE+

⚡ PoE+: IEEE 802.3at

⚡ Max power consumption: 30W

Interfaces

⚡ LAN: 10/100/1000BASE-TX with Auto-MDIX, RJ-45

⚡ Recommended cabling: CAT6 with MPTL

⚡ Active switch output: 12V / 0.6A DC

⚡ Passive switch: SSR NO up to 30V / 1A AC/DC

⚡ Inputs: 3 (passive/active mode, −30V to +30V DC)

⚡ VBus connector: yes

⚡ OSDP internal: yes (additional module combined with RFID reader)

⚡ Wiegand internal: yes (additional module combined with RFID reader)

⚡ Tamper switch: mechanical (additional module)

Supported Protocols

⚡ SIP 2.0, SIPS, DHCP opt. 66, SMTP, SNMP, TR069, 802.1x, RTSP, RTP, SRTP, TFTP, HTTP, HTTPS, Syslog, ONVIF

Audio

⚡ Microphones: 2 integrated

⚡ Amplifier: 10W / 4Ω

⚡ Speaker: 10W / 4Ω

⚡ Sound pressure level (SPL max): 94 dB (at 1kHz at 1m)

⚡ Induction loop: yes (internal module)

⚡ Volume control: adjustable with automatic adaptive mode

⚡ Full duplex: yes (AEC)

⚡ Speech transmission index (STI): 0.89

⚡ Protocols: RTP/RTSP/SRTP

⚡ Codecs: G.711, G.729, G.722, L16/16kHz

2N IP Force 2.0 IP Video Intercom 1 Button with Camera (9151301C)

½ Signalling protocol: SIP (UDP, TCP, TLS)

Camera & Video

½ Sensor sensitivity: 14000 e⁻/Lux-sec

½ Focal length: 1.935mm

½ View angle: 133°; (H), 112°; (V)

½ Infrared light: yes

½ WDR: yes

½ Minimum illumination: 0.1 lux without IR illumination

½ Protocols: RTP/RTSP/SRTP/HTTP, ONVIF v2.2 profile S and T

½ Codecs: H.264, H.265, MJPEG, Zipstream

½ Resolution H.264/H.265: max 2560 x 1920

½ Frame rate H.264/H.265: max 30fps at max resolution

½ Resolution MJPEG: max 1280 x 960

½ Frame rate MJPEG: max 15fps at max resolution

½ External camera: H.264 max 720p (1280 x 720) at 30fps

Other Physical Features

½ Material: aluminium (ADC12) with chromating Surtec 650

½ Surface treatment: powder coating

½ Buttons: 1 transparent backlit button

½ Cover rating: IP69, IK10 (EN 62262:2019)

½ Operating temperature: -30°C to +55°C

½ Storage temperature: -40°C to +70°C

½ Operating relative humidity: 10%–95% (non-condensing)

½ Maximum altitude: 2000m a.s.l.

½ Dimensions surface-mounted (W x H x D): 10.9 x 21.7 x 8.3 cm

½ Dimensions flush-mounted (W x H x D): 13.5 x 24.4 x 1.2 cm

½ Weight: 2000g

½ Warranty: 5-year

Package Contents

½ 1 x 2N IP Force 2.0 (9151301C) IP Video Intercom

Please Enquire