

2N IP One Black Video Door Intercom (9158106)



Product Name: 2N IP One Black Video Door Intercom (9158106)

Manufacturer: 2N Telecommunications

Model Number: 9158106

2N IP One Black Video Door Intercom (9158106)

2N IP One is a highly durable IP video intercom powered by the Axis ARTPEC-7 processor and designed for family homes. It comes equipped with a Full HD, 156-degree wide-angle camera for crystal clear video calls, and features Adaptive Face Zooming to ensure constant control over the front door and home surroundings. Slim frame, rounded edges – the 2N IP One is designed to impress. The colour of the eye-catching backlit button is customisable to the full RGB spectrum and indicates the current intercom's status: idle, ringing, in-call, or door open. With IP66 and IK08 certifications, the 2N IP One is truly durable. The body is made of high-quality anodised aluminium, ensuring exceptional resistance to vandals, water, and dust. Unlike regular video doorbells, you can connect a door strike directly to the 2N IP One, letting you remotely answer the door for a visitor, let them enter using a QR code, or open the door yourself using the My2N app. If motion is detected by the camera, or the microphone picks up increased noise, the 2N IP One will instantly notify residents and start recording what's happening outside the home. Based on open protocols and supporting multiple plug-ins, the intercom integrates with leading home automation and office building systems.

2N IP One Technical Specifications:

Power Supply

⌚½ Type: PoE and/or 12 V/1 A DC

⌚½ PoE: 802.3af (12.95 W max.)

Interfaces

⌚½ LAN: 10/100BASE-TX with Auto-MDIX, RJ-45 jack

⌚½ Recommended cabling: Cat-5e or better

⌚½ Active switch output: 12 V DC/max 600 mA

⌚½ Passive switch: NO contacts, 20V AC or 30V DC, 1A

⌚½ Inputs: 1 input - in passive/active mode (-30 V to +30 V DC); OFF = open or Uin > 1.5 V; ON = short-circuit or Uin < 1.5 V

⌚½ Tamper switch: yes

Audio

⌚½ Microphone: 1 integrated microphone

⌚½ Amplifier: 5 W RMS (Class D)

⌚½ Speaker: 1 integrated, 3W

⌚½ Volume control: adjustable with automatic adaptive mode

⌚½ Full duplex: Yes (AEC)

⌚½ Audio output: 3W

⌚½ Protocols: SIP/SIPS/RTP/SRTP/RTSP

⌚½ Codecs: G.711, G.729, G.722, L16/16kHz

Camera & Video

⌚½ Sensor: 1/2.7" colour CMOS

⌚½ Focal length: 1.93 mm

⌚½ View angle "peephole": 156°; (H), 116°; (V)

⌚½ Infrared light: yes

⌚½ WDR: yes

⌚½ Minimal illumination: 0.3 lux without IR illumination

⌚½ Protocols: RTP/RTSP/RTCP/HTTP, ONVIF v2.4 profile S

2N IP One Black Video Door Intercom (9158106)

• Codecs: H.264, MJPEG, Zipstream
• Resolution (H.264, MJPEG): max. 1920 x 1440 (4:3)
• Frame rate: max. 30 fps

Other Physical Features

• Frame (cover): aluminium casting
• Buttons: 1
• Processor: Axis ARTPEC-7
• Operating temperature: -40°C to +60°C
• Storage temperature: -40°C to +70°C
• Operating relative humidity: 10%-95% (non-condensing)
• Cover rating: IP66 and IK08
• Warranty: 5 years
• Dimensions (W x D x H): 7.8 x 5.3 x 17.2 cm

Package Contents

• 1 x 2N IP One (Black)

Please Enquire