

2N Fortis Handle Electronic Lever L-Shape Right (112044101R)



Product Name: 2N Fortis Handle Electronic Lever L-Shape Right (112044101R)

Manufacturer: 2N Telecommunications

Model Number: 112044101R

Please Note: This is the electronic lever (right-hand, L-shape) side of the handle only. A matching spindle and the opposite-side lever (mechanical or electronic) are sold separately.

2N Fortis Handle Electronic Lever L-Shape Right (112044101R)

The 2N Fortis Handle is a sleek, electronic door lever designed for busy, modern office environments. The stainless-steel body fits perfectly on wood, metal, aluminium, or even narrow-frame doors, with multiple spindle dimensions available for broad compatibility. It supports RFID credentials and will also offer mobile access in 2026. 2N Fortis wireless handles combine integrated electronics, LED indicators, and battery power in a sleek, compact, stainless-steel body that complements any commercial door. Durable mechanics, a long-life battery (up to 230,000 operations), and instant door opening with an RFID card ensure reliable performance in high-traffic environments. Install in minutes with no wiring and no drilling – just replace the old handle with an electronic one and extend your existing 2N access control to doors where cabling isn't an option. It protects doors with a robust handle that supports encrypted MIFARE®; DESFire®; credentials and meets modern cybersecurity standards. Manage access permissions and time profiles for your 2N Fortis Handle, alongside all 2N IP intercoms and Access Units, through the 2N Access Commander web interface. You can also set a short card validity period; if a card is lost, it will be blocked and stop working within 24 hours at the latest. 2N Fortis Handle Technical Specifications:

Power Supply

⌚½ Battery: 1x CR123A 3V

⌚½ Battery life cycle: Up to 230,000 openings (typically 4 years)

Dimensions

⌚½ Round rose: Diameter of 55mm

⌚½ L-shaped lever length: 140mm

⌚½ Spindle dimensions: 7mm, 8mm, 9mm

Interfaces

⌚½ RFID: 13.56MHz MIFARE®; DESFire®; (OSS-SO)

⌚½ NFC: 13.56MHz

⌚½ Bluetooth®; 2.4GHz BLE

Operational Mode

⌚½ Supported mode: Offline

Mechanical Properties

⌚½ Material: Nickel-plated brass

⌚½ Operating temperature: +5°C to 55°C

⌚½ Storage temperature: -40°C to 65°C

⌚½ Cover rating: None (indoor use only)

Door Specification

2N Fortis Handle Electronic Lever L-Shape Right (112044101R)

½ Door thickness: 30mm - 110mm

½ Door type: Wood, steel and aluminium

½ Frame type: Narrow or wide frame with backset of more than 28mm

Package Contents

½ 1 x 2N Fortis Handle, Electronic Lever, L-shape, Right

Please Enquire
