

Yealink T26P IP Phone (SIP-T26P)



Product Name: Yealink T26P IP Phone (SIP-T26P)

Manufacturer: -

Model Number: SIP-T26P

Please Note: The Yealink T26P has been discontinued. For an alternative, we recommend the Yealink T27P IP Phone (SIP-T27P).

Yealink T26P IP Phone (SIP-T26P)

The Yealink T26P is an advanced, high end HD VoIP Phone designed for everyday business use. The T26P is not only feature rich, but is also cost effective, affordable and includes a 132x64 graphic LCD screen, 3 VoIP accounts which are Broadsoft, Avaya, Asterisk validated, HD Voice and a TI TITAN chipset.

Yealink T26P (SIP-T26P) Key Features

- 3 SIP Accounts
- 132x64 White Backlit LCD Display
- 13 Programmable Keys
- 3 Indication LED's
- Power over Ethernet
- 3 Way Conference Calls
- Expansion Module Available.
- MP3 Ringtones and Voicemail.
- Call Hold, Waiting and Transfer.

Phone Connectivity

Note: Please refer to the Yealink VoIP Phone Range Detailed Comparison Table for more information.

Yealink T26P Technical Specifications

Phone Features

- 3 VoIP accounts, hotline, emergency call
- Call hold, call waiting, call forward, call return
- Caller ID display, Redial, Mute, DND
- Call transfer (blind/semi-attended/attended)
- Speed dial, SMS, voicemail
- Auto-answer, 3-way conferencing
- Tone scheme, volume control
- Message Waiting Indication (MWI) LED
- Phonebook (300 entries), blacklist
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Call history: dialed/received/missed/forwarded
- Menu-driven user interface
- Programmable soft keys
- Localised language and input method
- Supports up to 6 expansion modules (EXP38 and EXP39)
- Supports wireless headset adapter (EHS36)

Advanced Features

- XML phonebook search/import

Yealink T26P IP Phone (SIP-T26P)

• XML Browser, Hot-desking
• LDAP phonebook

VoIP PBX System Integration

• Busy lamp field (BLF), BLF list
• Bridged line appearance (BLA)
• DND & Forward synchronisation
• Call park, call pickup
• Intercom, Paging, Music on hold
• Call recording, call completion
• Group listening, group pickup
• Anonymous call, anonymous call rejection
• Network conference
• Distinctive ringtone
• Dial Plan, dial-now

Voice Features & Codecs

• Full-duplex speakerphone with AEC
• Wideband codec: G.722
• Narrowband codec: G.711µ/A, G.723.1
• G.726, G.729AB
• VAD, CNG, AEC, PLC, AJB, AGC

Network Features

• SIP v1 (RFC2543) & v2 (RFC3261)
• DNS SRV (RFC3263)
• NAT Traversal: STUN mode
• Redundant server support
• DTMF: In-Band, RFC2833, SIP Info
• Proxy mode and peer-to-peer SIP link mode
• IP Assignment: Static/DHCP/PPPoE
• Bridge/router mode for PC port
• Telnet/HTTP/HTTPS server
• TFTP/DHCP/PPPoE client
• DNS client, NAT/DHCP server
• Logout

Phone Management

• Auto-provision with PnP
• Auto-provision via FTP/TFTP/HTTP/HTTPS
• SNMP V1/2 optional, TR069 optional
• Configuration: browser/phone/auto-provision
• Customised factory configuration
• Trace package and system log export

Phone Security

• Phone lock for personal privacy protection
• Admin/VAR/User 3-level configuration mode
• Open VPN, 802.1x, VLAN QoS (802.1pq)
• Transport Layer Security (TLS)

Yealink T26P IP Phone (SIP-T26P)

• 1/2 HTTPS (server/client), SRTP (RFC3711)
• 1/2 Digest authentication using MD5/MD5-sess
• 1/2 Secure configuration file via AES encryption

Physical Specification

• 1/2 TI TITAN chipset
• 1/2 45 keys (including 13 programmable)
• 1/2 132 x 64 graphic LCD
• 1/2 1 x RJ9 (4P4C) handset port
• 1/2 2 x RJ45 10/100M Ethernet ports
• 1/2 1 x RJ9 (4P4C) headset port
• 1/2 1 X RJ12 (6P6C) EXT port
• 1/2 Power adapter: AC 100~240V input and DC 5V/1.2A output (Optional)
• 1/2 Power over Ethernet (IEEE 802.3af)
• 1/2 Power consumption: 1.6-2.6W
• 1/2 Dimension: 273 x 204 x 42mm
• 1/2 Operating humidity: 10~95%
• 1/2 Storage temperature: up to 60°C
• 1/2 Net weight: 1.05KG

Please Enquire

Options available for Yealink T26P IP Phone (SIP-T26P) :

Power Supply Required?

[UK PSU required \(+\\$5.34\)](#), [EU PSU required \(+\\$5.34\)](#), [None - Using PoE](#).

RPS Extension ID

[TEXT.](#)

RPS Extension Password

[TEXT.](#)

RPS Display Name

[TEXT.](#)

RPS PBX URL

[TEXT.](#)

RPS NAT Enabled

[TEXT.](#)

RPS Outbound Proxy

[TEXT.](#)

RPS SIP Port

[TEXT.](#)

RPS Enable Outbound Proxy

RPS Own Server URL

Yealink T26P IP Phone (SIP-T26P)

RPS Own Server Name

Yealink EXP38 IP Phone Expansion Module

Required (+\$89.59), Not Required.

Yealink EXP39 IP Phone Expansion Module

Required (+\$117.34), Not Required.