Yealink T28P IP Phone (SIP-T28P)



Product Name: Yealink T28P IP Phone (SIP-T28P)
Manufacturer: -
Model Number: SIP-T28P

Yealink T28P IP Phone (SIP-T28P)

Please Note: The Yealink T28P has been discontinued. For an alternative, we recommend the Yealink T29G.

The Yealink T28P is a top of the range business VoIP phone, featuring high quality telephony features including a 320 x 160 graphic LCD screen with 4-level grayscales, 6 VoIP accounts which are Broadsoft / Avaya/ Asterisk validated, and the TI TITAN chipset.
Yealink SIP-T28P Features

ï¿½ 6 SIP Accounts
ï¿½ 320x160 White Backlit LCD Display
ï¿½ 4 Level Grayscales
ï¿½ 16 Programmable Keys
ï¿½ Logo Customisation on Screen
ï¿½ Expansion Keypad Available
ï¿½ Power over Ethernet
ï¿½ 3 Way Conference Calls
ï¿½ Speakerphone
ï¿½ MP3 Ringtones and Voicemail.
ï¿½ Call Hold, Waiting and Transfer.

Note: Please refer to the Yealink VoIP Phone Range Detailed Comparison Table for more information.
Yealink T28P Technical Specifications
Phone Features

ï¿½ 6 VoIP accounts, Hotline, Emergency call
ï¿½ Call hold, Call waiting, Call forward, Call return
ï¿½ Call transfer (blind/semi-attended/attended)
ï¿½ Caller ID display, Redial, Mute, DND
ï¿½ Auto-answer, 3-way conferencing
ï¿½ Speed dial, SMS, Voicemail
ï¿½ Message Waiting Indication (MWI) LED
ï¿½ Tone scheme, Volume control
ï¿½ Direct IP call without SIP proxy
ï¿½ Ring tone selection/import/delete
ï¿½ Phonebook (300 entries), Black list
ï¿½ Call history: dialed/received/missed/forwarded
ï¿½ Menu-driven user interface
ï¿½ Localized language and input method
ï¿½ Soft keys programmable
ï¿½ Supports up to 6 expansion modules(EXP38 and EXP39)
ï¿½ Supports Wireless Headset Adapter (EHS36)

Advanced Features

ï¿½ XML phonebook search/import
ï¿½ LDAP phonebook

Yealink T28P IP Phone (SIP-T28P)

ï¿½ XML Browser, Hot-desking
ï¿½ PUSH XML
ï¿½ Action URL & Active URI

IP PBX System Integration

ï¿½ Busy lamp field (BLF), BLF list
ï¿½ Bridged line appearance (BLA)
ï¿½ DND & Forward synchronization
ï¿½ Intercom, Paging, Music on hold
ï¿½ Call park, Call pickup
ï¿½ Call recording, Call completion
ï¿½ Group listening, Group pickup
ï¿½ Anonymous call, Anonymous call rejection
ï¿½ Network conference
ï¿½ Distinctive ringtone
ï¿½ Dial Plan, Dial-now

Codecs and Voice Features

ï¿½ Wideband codec: G.722
ï¿½ Narrowband codec: G.711µ/A, G.723.1
ï¿½ G.726, G.729AB
ï¿½ VAD, CNG, AEC, PLC, AJB, AGC
ï¿½ Full-duplex speakerphone with AEC

Network Features

ï¿½ SIP v1 (RFC2543), v2 (RFC3261)
ï¿½ IPV6
ï¿½ DNS SRV (RFC3263)
ï¿½ Redundant server support
ï¿½ NAT Traversal: STUN mode
ï¿½ DTMF: In-Band, RFC2833, SIP Info
ï¿½ Proxy mode and peer-to-peer SIP link mode
ï¿½ IP Assignment: Static/DHCP/PPPoE
ï¿½ Bridge/router mode for PC port
ï¿½ TFTP/DHCP/PPPoE client
ï¿½ Telnet/HTTP/HTTPS server
ï¿½ DNS client, NAT/DHCP server
ï¿½ Logout

Management

ï¿½ Auto-provision via FTP/TFTP/HTTP/HTTPS
ï¿½ Auto-provision with PnP
ï¿½ SNMP V1/2 optional, TR069 optional
ï¿½ Configuration: browser/phone/auto-provision
ï¿½ Factory configuration customized
ï¿½ Trace package and system log export

Security

ï¿½ Open VPN, 802.1x, VLAN QoS (802.1pq), LLDP
ï¿½ Transport Layer Security (TLS)

Yealink T28P IP Phone (SIP-T28P)

ï¿½ HTTPS (server/client), SRTP (RFC3711)
ï¿½ Digest authentication using MD5/MD5-sess
ï¿½ Secure configuration file via AES encryption
ï¿½ Phone lock for personal privacy protection
ï¿½ Admin/VAR/User 3-level configuration mode

Connectivity

Physical Features

ï¿½ TI TITAN chipset
ï¿½ 320 x 160 graphic LCD with 4-level grayscales
ï¿½ 48 keys including 16 programmable keys
ï¿½ 1 x RJ9 (4P4C) handset port
ï¿½ 1 x RJ9 (4P4C) headset port
ï¿½ 2 x RJ45 10/100M Ethernet ports
ï¿½ 1 x RJ12 (6P6C) EXT port
ï¿½ Power adapter: AC 100~240V input and DC 5V/1.2A output (Optional)
ï¿½ Power over Ethernet (IEEE 802.3af)
ï¿½ Power consumption: 1.6-2.6W
ï¿½ Net weight: 1.05KG
ï¿½ Dimension: 273 x 204 x 42mm
ï¿½ Operating humidity: 10~95%
ï¿½ Storage temperature: up to 60°C

Yealink T28P Certifications

Please Enquire

Options available for Yealink T28P IP Phone (SIP-T28P) :

Power Supply Required?
None - Using PoE, UK PSU required (+£3.99), EU PSU required (+£3.99).

RPS Extension ID
TEXT.

RPS Extension Password
TEXT.

RPS Display Name
TEXT.

RPS PBX URL
TEXT.

RPS NAT Enabled
TEXT.

RPS Outbound Proxy
TEXT.

Yealink T28P IP Phone (SIP-T28P)

RPS SIP Port
TEXT.

RPS Enable Outbound Proxy

RPS Own Server URL

RPS Own Server Name

Yealink EXP38 IP Phone Expansion Module
Not Required, Required (+£67.00).

Yealink EXP39 IP Phone Expansion Module
Not Required, Required (+£87.75).