

## CyberData VoIP Loudspeaker Amplifier Wireless (010860)



Product Name: CyberData VoIP Loudspeaker Amplifier Wireless (010860)

Manufacturer: -

Model Number: 010860

Availability: Discontinued

Please note that the VoIP Loudspeaker Amplifier Wireless has been replaced by the V2 VoIP Loudspeaker Amplifier Wireless

The CyberData SIP-enabled VoIP Loudspeaker Amplifier provides an easy method for implementing an IP-based overhead paging system. The Amplifier is designed for noisy environments such as warehouses and shop floors. It comes with a weatherproof NEMA enclosure. The interface is compatible with most SIP-based IP PBX servers that comply with the SIP RFC 3261. For non-SIP environments, the Amplifier can be configured to listen to multicast address and port number combinations to form paging zones. Power-over-Ethernet (802.3af) and a wireless option are available. Features

- SIP (RFC 3261) compatible
- Dual-Speed Ethernet 10/100 Mbps
- Web-based configuration
- Web-based firmware upgradeable
- PoE 802.3af Enabled (Powered-over-Ethernet)
- Wireless 802.11g option
- IGMP
- Weatherproof enclosure

### Specifications

- VoIP Loudspeaker Amplifier Specifications
- Ethernet I/F 10/100 Mbps
- Power Input PoE 802.3af or 110-230VAC PS
- Protocol SIP RFC 3261
- Payload Types G711
- Regulatory Compliance FCC Class B, UL 60950
- Warranty 2 Years Limited
- Dimensions 14" x 10" x 4"
- Part Number See back
- Enclosure NEMA Type 3R/IP42
- Output - With one 8 Ohm speaker, up to 8 watts output. - With external PoE power injector (Part #010867) and one 8 Ohm speaker, up to 10 watts output.

**Please Enquire**