

Atcom IP02 IP PBX



Product Name: Atcom IP02 IP PBX

Manufacturer: -

Model Number: IP02

Please Note: This product has been discontinued. Please see our IP PBX range.

Atcom IP02 IP PBX Appliance

Please Note: An understanding of both Linux and Asterisk command line is required for the successful configuration of the Atcom IP0x. VoiPon offers paid for support options for customers who experience difficulty configuring this PBX, which can be selected from the options below.

The Atcom IP02 IP PBX is a complete Asterisk appliance with either one FXO or FXS module. It is an embedded open source Linux system with built-in SIP/IAX proxy server and NAT functions. The IP-02 provides a solid, uniform platform for traditional PSTN communications in addition to VoIP communications

Features

- 2 FXO/FXS Ports
- Supports SIP Protocol
- Easy to configure and install
- Smart IVR system
- Unlimited recording

Atcom IP02 - Technical Specification PBX Features

- Basic Features: Blacklist, Caller ID, Call Back, Call Detail Records (CDR), Call Pickup (Group Pickup & Directed Pickup), Call Parking, Call Queues, Call Recording, Call Routing, Call Transfer (Blind Transfer & Attend Transfer), Call Waiting, Conference, Do Not Disturb (DND), Follow me, Interactive Voice Response (IVR), Intercom/Paging, Music on Hold (MoH), Ring Group, Skype Integration (Skype for SIP), Voice Mail, Voice Mail to Email
- Advanced Features: Call Recording, Direct Inward System Access (DISA), Dual-OS Redundancy, External Storage Supported, IP Restriction, Personal Web Portal, Storage Quota, Privilege, Diagnostic Tool, Customised DialPlan, Auto Provisioning.
- Audio Codec : G.711(A/μ), G.722, G.726, G.729, GSM, Speex, ADPCM
- Video Codec: H.261, H.263, H.263P, H.264

Hardware Features

- LAN Port: 1 10 / 100Mbps
- WAN Port: 1 10 / 100Mbps
- Analog Port: 2 RJ11
- ATCOM Telephony Module supported: 1 Port FXO or 1 Port FXS

Network Features

- DHCP Server / Client: Yes
- DDNS: Yes
- Static IP: Yes
- VLAN (802.1Q): Yes
- VPN: Yes (PPTP VPN supported)
- Security: Yes (Firewall)

Atcom IP02 IP PBX

1 Port: Forward

SIP Features

1 SIP Compatibility: SIP(RFC3261)

1 Concurrent Calls: 8

1 Maximum Registered Users

1 Supported: 64

Installation & Configuration

1 Installation: Desktop or Wall mount

1 Configuration: Web-based configuration

Others

1 Power Consumption: 5W

1 Storage Temperature: 20°C - 65°C (-4°F - 149°F)

1 Operating Temperature: 0°C - 40°C (32°F - 104°F)

1 Operating Humidity: 10 - 90%, Non-condensing

1 Dimension: 100 x 100 x 28mm

1 Weight: 0.35 Kg

Price: £137.10

Options available for Atcom IP02 IP PBX :

Port 1 - FXO/FXS

- Not Required -, 1 x Dual FXO Module (+£57.00), 1 x FXO port and 1 x FXS port (+£57.00), 1 x Dual FXS Module (+£57.00).

Warranty

IP01/IP02 12 Month Warranty, IP01/IP02 Additional 12 Month Warranty (+£50.00).

Annual Support Maintenance

- Not Required -, Require Annual Support (+£480.00).