

## Netgear Prosafe FS108P 8-Port 10/100 Switch with 4-Port POE



Product Name: Netgear Prosafe FS108P 8-Port 10/100 Switch with 4-Port POE Manufacturer: -Model Number: FS108P

Please Note: This product has been discontinued. Please see the Netgear Prosafe GS108PE.

Netgear Prosafe FS108P 8-Port 10/100 Switch with 4-Port POE The Netgear ProSafe 8-Port 10/100 Switch provides power and data from a single point, using Power over Ethernet (PoE) over a single Cat-5 cable. The eight Fast Ethernet ports can be used for any 10/100 Mbps link and four of these ports can supply industry-standard IEEE 802.3af power.

Key features

 $i_{2}$  Supply power to wireless access points and surveillance cameras over Cat-5 cabling  $i_{2}$  IEEE 802.3af power on up to 4 ports

ï¿1/2 8 10/100 Mbps Ports with AutoUplink™

Advanced auto-sensing algorithm gives power only to 802.3af end devices, so no need to worry about damaging proprietary PoE or non-PoE equipment.

In addition, it discontinues the power when PoE devices are disconnected. Easy and reliable, the ProSafe 8-Port 10/100 Switch automatically determines PoE requirements, speed, duplex, and cable type using AutoUplink®.

The affordably priced ProSafe 8-Port 1-/100 Switch delivers PoE to any small business network that wants to simplify the installation of wireless access points and IP-based surveillance cameras. These devices are optimally installed on a ceiling or high on a wall, away from most electrical outlets. PoE eliminates the requirement for a dedicated electrical outlet to power these devices. This allows for flexibility in situating devices where AC power is difficult to access and lowers installation costs. Compact and flexible, the ProSafe is ideal for small business network that want to inexpensively use PoE to deploy wireless access points and IP-based network surveillance cameras.

Flexible Choose to plug in up to eight Ethernet or Fast Ethernet devices and mix in up to four 802.3af IP-based devices like wireless access points or IP-based network surveillance cameras. Place these 802.3af-compliant devices where they belong - high up on walls and ceiling for maximum coverage - or anywhere else you need them. Power and data are carried over standard Cat-5 cabling.

Plug and Play The standards-based ProSafe FS108P senses and adjusts for network speed and cabling type automatically, for easy integration into your existing 10/100 Ethernet network. For PoE, the switch automatically detects 802.3af-compliant devices, and supplies power as needed. Front panel LEDs keep you informed of switch and PoE status.

Quiet and Compact Engineered for compact convenience, it features a 9-inch, durable metal case that is easily positioned on your desktop or a wall, using the included mounting hardware. The fan-less design quietly integrates in your small office environment.

Great Value With data switching and Power over Ethernet integrated into one unit, the FS108P saves space, reduces cables and eliminates the requirement for dedicated electrical outlets - lowering installation costs, simplifying installation of PoE-capable devices, and eliminating the need for electricians or extension cords. All in all a great benefit for a modest price.

Netgear 8 Port Switch with 4 PoE Ports - Technical Specifications Network Ports

ï¿1/2 8 auto speed-sensing 10/100 RJ-45 ports

Network Protocol and Standards



## Netgear Prosafe FS108P 8-Port 10/100 Switch with 4-Port POE

i¿½ IEEE 802.3i 10BASE-T i¿½ IEEE 802.3u 100BASE-TX i¿½ IEEE 802.3x Flow Control i¿½ IEEE 802.3af DTE Power via MDI

**Performance Specifications** 

i¿½ Forwarding modes: Store-and-forward
i¿½ Bandwidth: 1.6 Gbps
i¿½ Network latency: Less than 20 μs for 64-byte frames in store-and-forward mode for 100 Mbps to 100 Mbps transmission
i¿½ Buffer memory: 96 KB embedded memory per unit
i¿½ Address database size:1,000 media access control (MAC) addresses per system
i¿½ Addressing: 48-bit MAC address
i¿½ Mean Time Between Failure (MTBF): 190,000 hours (~ 21 years)
i¿½ Acoustic Noise: 0 dB

Status LEDs

� System: Power, PoE Maximum Power � Per Port: Link, Activity, Speed, PoE Active, PoE Fault

Power Supply

� Total Power Consumption: 44 W maximum
� PoE Watt budget: 32W
� 802.3af Power Consumption: 32 W maximum (Ports 1 – 4)
� 48VDC, 0.8A power output; plug is localized to country of sale

**Physical Specifications** 

� Dimensions (H x W x D): 1.1 x 9.3 x 4.1 in. (27 x 235 x 103 mm) � Weight: 1.7 lbs. (0.74 kg)

**Environmental Specifications** 

ï¿1/2 Operating temperature: 32 to 104°F (0 to 40° C)

ï¿1/2 Storage temperature: 14 to 158°F (-10 to 70°C)

ï¿1/2 Operating humidity: 90% maximum relative humidity, non-condensing

ï¿1/2 Storage humidity: 95% maximum relative humidity, non-condensing

ï¿1/2 Operating altitude: 10,000 ft (3,000 m) maximum

ï¿1/2 Storage altitude: 10,000 ft (3,000 m) maximum

Electromagnetic Emissions

i¿½ CE mark, commercial i¿½ FCC Part 15 Class B i¿½ VCCI Class B i¿½ EN 55022 (CISPR 22), Class B i¿½ C-Tick

**Electromagnetic Immunity** 

� EN 55024



## Netgear Prosafe FS108P 8-Port 10/100 Switch with 4-Port POE

Safety

ii 2<sup>1</sup>/<sub>2</sub> CE mark, commercial ii 2<sup>1</sup>/<sub>2</sub> CE/LVD EN60950

Warranty

i¿½ NETGEAR Lifetime Warranty† i¿½ 2 years for power supply

Package Contents

� ProSafe 8 Port 10/100 Switch with Power over Ethernet (FS108P)
� AC Adapter
� Wall-mount kit
� Installation guide
� Warranty/Support Information card

## **Please Enquire**