

Citel C4110 SIP + IAX VoIP Phone



Product Name: Citel C4110 SIP + IAX VoIP Phone

Manufacturer: -

Model Number: C4110

Citel C4110 SIP + IAX VoIP Phone

Citel C4110 SIP + IAX VoIP Phone is a 3 Line desktop VoIP phone that delivers high voice quality and is packed with features. It supports both IAX2 and SIP protocols.

The Citel C4110 can easily be configured via a web browser, and also supports convenience auto-provisioning via TFTP server. The C4110 features 8 distinctive ring tones, volume and ringer level control, and voicemail retrieval via keypad or programmable keys. With an integrated 2 port 10/100 MBPs switch, 802.3af Power Over Ethernet, RJ9 headset jack and VLAN/DHCP support. This phone is PoE compatible; however power supply units are also available.

- Two lines / call appearances with LEDs
- Conference calling (with or without server)
- Call transfer (blind or consultative)
- Call hold, call waiting, and call forwarding
- Caller ID and Call-waiting caller ID
- Do not disturb
- Number note pad
- Paging
- Auto answer
- Configurable dial plan
- 500 entry phone book
- Keypad dialing
- Speed dial from phone book and call log
- 100 number redial list
- Menu layout for easy navigation via softkey
- Missed / outgoing / incoming call logs, 100 entries each voicemail retrieval via keypad or programmable keys
- 8 distinctive ring tone
- Volume and Ringer level control
- 4 or 12 (with expansion module) programmable keys for speed dial or feature access.
- Spanish, French, Chinese and English language compatible.

Citel C4110 SIP + IAX VoIP Phone Technical Specification Protocols Supported

- SIP (RFC3261, RFC3262)
- IAX2
- SDP (RFC2327)
- (SIP) Subscribe / Notify (RFC3265)
- (SIP) Offer / Answer Model (RFC3264)
- (SIP) Refer Method (RFC3515)
- DTMF transport (RFC2833)
- SIP INFO and in-band DTMF transport
- RTP / RTCP (RFC3550, 3551)
- (SIP) DNS SRV (RFC2781)

Audio / Codec:

- G.711 A law and G.711 U law 64K
- G.729

Citel C4110 SIP + IAX VoIP Phone

- G.723.1
- DTMF tone Generation
- Acoustic echo cancellation
- Built-in audio mixer

Voice Protocols

- SIP (per IETF-SIP-RFC3261)
- IAX2
- RTP
- G.711 u-law
- G.711 A-law
- G.729 A/B
- Silence Suppression
- Comfort Noise Generation
- G.168 Echo Cancellation

Price: Â£75.00

Options available for Citel C4110 SIP + IAX VoIP Phone :

Power Supply Required?

- Not Required -, [Power Supply For C4110 \(+Â£10.00\)](#).