

## Cisco SPA508G IP Phone



Product Name: Cisco SPA508G IP Phone

Manufacturer: Cisco Systems

Model Number: SPA-508G

Please Note: The Cisco SPA508G IP Phone is PoE (Powered-Over-Ethernet) and does not include a mains Power Supply. If mains power is required, this can be added via the drop down menu above.

### Cisco SPA 508G IP Phone

The Cisco SPA508G is an 8-line IP Phone with PoE, a 2-Port Switch and a Full Duplex Speakerphone. The SPA508G has been rigorously tested to make certain of full compatibility with equipment from VoIP infrastructure leaders and means service providers to quickly deliver competitive, feature-rich services to their customers.

### Cisco SPA508G IP Phone Key Features

- Full-featured 8-line business-class IP phone supporting Power over Ethernet (PoE)
- Wideband audio for unsurpassed voice clarity and enhanced speaker quality
- Cisco HD Voice sound
- Monochrome backlit display for ease of use, aesthetics, and on-screen applications
- Full Duplex Speakerphone
- Headset port
- Call transfer, call waiting, call conferencing
- Supports up to two Cisco SP500S Expansion Module, adding up to 64 additional buttons

### Carrier-Grade Security, Provisioning, and Management

The Cisco SPA 508G uses standard encryption protocols to perform highly secure remote provisioning and unobtrusive in-service software upgrades. Remote provisioning tools include detailed performance measurement and troubleshooting features, enabling network providers to deliver high-quality support to their subscribers. Remote provisioning also saves service providers the time and expense of managing, preloading, and reconfiguring customer premises equipment.

### Comprehensive Interoperability and SIP-Based Feature Set

With hundreds of features and configurable service parameters, the Cisco SPA508G IP Phone addresses the requirements of traditional business users while building on the advantages of IP telephony. Features such as easy station moves and shared line appearances (across local and geographically dispersed locations) are just some of the many advantages of the SPA508G. The SPA 508G IP Phone also supports productivity-enhancing features such as VoiceView Express, and Cisco XML applications when used with the Cisco Unified Communications 500 Series in SPCP mode.

Note: Please refer to the Cisco VoIP Detailed Comparison Table for more information.

### Cisco SPA508G IP Phone Technical Specifications

#### Telephony Features

- Eight voice lines
- Eight independent SIP Registrations
- Line status: active line indication, with name and number
- Menu-driven user interface
- Shared line appearance
- Speakerphone
- Call hold
- Music on hold
- Call waiting

## Cisco SPA508G IP Phone

- Caller ID name and number
- Outbound caller ID blocking
- Call transfer: attended and blind
- Three-way call conferencing with local mixing
- Multiparty conferencing via external conference bridge
- Automatic redial of last calling and last called numbers
- On-hook dialing
- Call pickup: selective and group
- Call park and unpark
- Call swap
- Call back on busy
- Call blocking: anonymous and selective
- Call forwarding: unconditional, no answer, on busy
- Hot line and warm line automatic calling
- Call logs (60 entries each): made, answered, and missed calls
- Redial from call logs
- Personal directory with auto-dial (100 entries)
- Do not disturb
- Digits dialled with number auto-completion
- Anonymous caller blocking
- Uniform Resource Identifier (URI) (IP) dialling support (vanity numbers)
- On-hook default audio configuration (speakerphone and headset)
- Multiple ring tones with selectable ring tone per line
- Called number with directory name matching
- Ability to call number using name: directory matching or via caller ID
- Subsequent incoming calls show calling name and number
- Date and time with support for intelligent daylight savings
- Call start time stored in call logs
- Call timer
- Name and identity (text) displayed at startup
- Distinctive ringing based on calling and called number
- 10 user-downloadable ring tones
- Speed dialling, eight entries
- Configurable dial/numbering plan support
- Intercom
- Group Paging
- Network Address Translation (NAT) Traversal, including Simple Traversal of UDP Through NATs (STUN) support
- DNS SRV and multiple A records for proxy lookup and proxy redundancy
- Syslog, debug, report generation, and event logging
- Highly secure call encrypted voice communications support
- Built-in web server for administration and configuration with multiple security levels
- Automated remote provisioning, multiple methods; up to 256-bit encryption (HTTP, HTTPS, Trivial File Transfer Protocol [TFTP])
- Option to require administrator password to reset unit to factory defaults

### Hardware Features

- Pixel-based display: 128 x 64 monochrome LCD graphical display with backlight
- Dedicated illuminated buttons for: Audio mute on/off, Headset on/off, Speakerphone on/off
- 4-way rocking directional knob for menu navigation
- Voicemail message waiting indicator (VMWI) light
- Voicemail message retrieval button
- Dedicated hold button
- Settings button for access to feature, setup, and configuration menus

## Cisco SPA508G IP Phone

- Volume control rocking up/down knob controls handset, headset, speaker, ringer
- Standard 12-button dialling pad
- High-quality handset and cradle
- Built-in high-quality microphone and speaker
- Headset jack: 2.5 mm
- LED test function
- Two Ethernet ports with integrated Ethernet switch: 10/100BASE-T RJ-45
- 802.3af-compliant PoE
- Optional 5 VDC universal (100-240V) switching; power supply is ordered separately (Cisco PA100)

### Data Networking

- MAC address (IEEE 802.3)
- IPv4 (RFC 791)
- Address Resolution Protocol (ARP)
- DNS: A record (RFC 1706), SRV record (RFC 2782)
- Dynamic Host Configuration Protocol (DHCP) client (RFC 2131)
- Internet Control Message Protocol (ICMP) (RFC 792)
- TCP (RFC 793)
- User Datagram Protocol (UDP) (RFC 768)
- Real-Time Transport Protocol (RTP) (RFC 1889, 1890)
- Real Time Control Protocol (RTCP) (RFC 1889)
- Differentiated Services (DiffServ) (RFC 2475)
- Type of service (ToS) (RFC 791, 1349)
- VLAN tagging 802.1p/Q: Layer 2 quality of service (QoS)
- Simple Network Time Protocol (SNTP) (RFC 2030)
- Cisco Discovery Protocol (CDP)
- Link Layer Discovery Protocol (LLDP)

### Voice Gateway

- SIP version 2 (RFC 3261, 3262, 3263, 3264)
- SPCP with the Cisco Unified Communications 500 Series
- SIP proxy redundancy: dynamic via DNS SRV, A records
- Reregistration with primary SIP proxy server
- SIP support in NAT networks (including STUN)
- SIPFrag (RFC 3420)
- Secure (encrypted) calling via SRTP
- Codec name assignment
- Voice algorithms: G.711 (A-law and  $\mu$ -law), G.726 (16/24/32/40 kbps), G.729 A, G.722
- Dynamic payload support
- Adjustable audio frames per packet
- Dual-tone multifrequency (DTMF), in-band and out-of-band (RFC 2833) (SIP INFO)
- Flexible dial plan support with interdigit timers
- IP address/URI dialling support
- Call progress tone generation
- Jitter buffer: adaptive
- Frame loss concealment
- Comfort Noise Generation (CNG)
- Voice activity detection (VAD) with silence suppression
- Attenuation/gain adjustments
- VMW/Voice email waiting indicator, via NOTIFY, SUBSCRIBE
- Caller ID support (name and number)
- Third-party call control (RFC 3725)

## Cisco SPA508G IP Phone

### Provisioning, Administration, and Maintenance

- Integrated web server provides web-based administration and configuration
- Telephone keypad configuration via display menu/navigation
- Automated provisioning and upgrade via HTTPS, HTTP, TFTP
- Asynchronous notification of upgrade availability via NOTIFY
- Nonintrusive in-service upgrades
- Report generation and event logging
- Statistics transmitted in BYE message
- Syslog and debug server records: configurable per line

### Power Supply

- Power supply is optional and is purchased separately
- Models: Cisco PA100-NA, PA100-EU, PA100-UK, PA100-AU
- DC output voltage: +5 VDC at 2.0A maximum
- Switching power adapter: 100-240V 50-60 Hz AC input

### Physical Interfaces

- Two 10/100BASE-T RJ-45 Ethernet ports (IEEE 802.3)
- Handset: RJ-9 connector
- Built-in speakerphone and microphone
- Headset 2.5mm jack

### Security Features

- Password-protected system, preset to factory default
- Password-protected access to administrator and user-level features
- HTTPS with factory-installed client certificate
- HTTP digest: encrypted authentication via MD5 (RFC 1321)
- Up to 256-bit Advanced Encryption Standard (AES) encryption
- SIP over Transport Layer Security (TLS)
- Secure Real-Time Transport Protocol (SRTP)

### Package Contents

- Cisco SPA 508G IP Phone, handset, and stand
- Handset Cord
- RJ-45 Ethernet cable
- Quick-Start Guide
- CD

### Physical

- Body Dimensions (W x H x D): 8.42 x 8.35. x 1.73in. (214 x 212 x 44 mm)
- Unit Weight: 2.00 lb ( 0.9 kg)
- Operating Temperature: 32°F; ~ 104°F (0°C; ~ 40°C)
- Storage Temperature: -4°F; ~ 158°F (-20°C; ~ 70°C)
- Operating Humidity: 5% to 95% noncondensing
- Storage Humidity: 5% to 95% noncondensing

### Regulatory Compliance

## Cisco SPA508G IP Phone

iC1/2 FCC (Part 15, Class B)  
iC1/2 CE Mark  
iC1/2 A-Tick  
iC1/2 C-Tick  
iC1/2 Telepermit  
iC1/2 UL  
iC1/2 CB

**Price: £120.00**

Options available for Cisco SPA508G IP Phone :

### **Power Supply Required**

Not Required, [Cisco PSU PA100 \(+£13.00\)](#).