

Valcom VIP-402 Lay In Ceiling Speaker



Product Name: Valcom VIP-402 Lay In Ceiling Speaker

Manufacturer: -

Model Number: VIP-402

Availability: In Stock

Valcom VIP-402 Lay In Ceiling Speaker

The VIP-402/VIP-402-EC Lay-In One-Way IP Ceiling Speaker enables voice access to a single zone of one-way paging over an IP-based LAN/WAN. This allows a page zone extension anywhere on the network. The speaker level is electrically adjusted during setup. The VIP-402 grille is made of steel with a white baked enamel finish and easily replaces a 2' x 2' or œ of a 2' x 4' ceiling tile. The VIP-402-EC replaces a 600mm x 600mm ceiling tile. Power is provided to the unit via a Power over an Ethernet switch meeting the 802.3af specification. Accessible as specific SIP end point and accessible as a multicast group member. Valcom multicast group paging features robust grouping and priority controls. This makes it easy to distribute low priority announcements yet allow high priority paging to overide ongoing announcements. An absolute priority can be assigned to allow for emergency override in any circumstance. Group paging priorities work locally or across the network in the same fashion allowing facility wide emergency paging. Valcom VIP-402 Lay In Ceiling Speaker Features

- � 802.3AF POE Power ONLY
- ï¿1/2 Replaces a 2' x 2' tile
- � Easy to install
- 12.1/2 No cutting tiles, no broken tiles, no mess
- � Excellent music and voice quality
- ï¿1/2 Built-in volume settings
- � Durable white acrylic baked enamel finish

Valcom VIP-402 Lay In Ceiling Speaker Core Features

- ï¿⅓ SIP And Multicast Enabled
- � Easy To Install via RJ-45
- � PoE (802.3af)
- � Live, Recorded Or Scheduled Messages
- ī¿½ Easily Connect Loudspeaker System To Existing Computer Networks
- ī¿½ Compatible With Cisco, Nortel, Avaya And Most IP Telephone Systems
- ï¿⅓ One-Way Paging
- ï¿⅓ Web Interface For Control And Setup
- ï¿⅓ Can Operate Over Secure Networks
- ï¿⅓ Paging Prioritization
- � Background Music
- � Web-based Firmware Upgradeable
- ï¿⅓ High Efficiency
- īപ്2 Line Out Supports Amplified Speakers
- ï¿⅓ Wireless Option
- ï¿⅓ Synchronized Clock Option
- ï¿⅓ Full Supervision
- ï¿⅓ Wireless Option
- ï¿⅓ Test / Setup Tones
- � Software Developer Kit Available
- 12.1/2 Compatible With Text/Audio To IP Telephones
- i¿1/2 Supports Syn-Apps, Checkmate, PagePro IP
- � DHCP

Valcom VIP-402 Lay In Ceiling Speaker Specifications Power



Valcom VIP-402 Lay In Ceiling Speaker

� External: 24 VDC @ 325 ma � POE: 802.3af, class 3

Networking

 \ddot{i} 10/100 Mbps Ethernet port

រ៉េះ 1 Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup.

ï¿⅓ Time and date synchronization using SNTP

Protocols

ï¿⅓ IETF SIP (RFC3261)

ï¿1/2 IETF IGMP version 3 (RFC3376)

ï¿1/2 IETF RTP (RFC1889)

ï¿⅓ IETF RFC2833

ï¿⅓ Digest Authentication

Dimensions and Weight

� Dimensions: 23.75" H x 23.75" W x 4.25" D (60.3 cm x 60.3 cm x 10.8 cm)

� Weight: 6.25 lbs (2.83 kg)

Price: £606.40