

## Valcom VIP-120-IC One Way SIP Ceiling Speaker



Product Name: Valcom VIP-120-IC One Way SIP Ceiling Speaker

Manufacturer: -

Model Number: VIP-120-IC

Availability: In Stock

Valcom VIP-120-IC One Way SIP Ceiling Speaker

The VIP-120-IC One-Way IP Ceiling Speaker enables voice access to a single zone of one-way paging over an IP-based LAN/WAN. This allows a page zone extension anywhere on the network. The speaker level is electrically adjusted during set up. The enclosure is made of steel with a durable white powder coated finish. Power is provided to the VIP-120 via a Power over an Ethernet switch meeting the 802.3af specification.

Valcom VIP-120-IC SIP Celing Speaker Features

- 12/2 Exceptional Voice & Music Reproduction
- � Contains Its Own Built-In Amplifier
- آزٰ White Epoxy Finish
- � Volume Control

Valcom VIP-120-IC SIP Celing Speaker Core Features

- ï¿⅓ SIP And Multicast Enabled
- � Easy To Install via RJ-45
- � PoE (802.3af)
- � Live, Recorded Or Scheduled Messages
- ī¿½ Easily Connect Loudspeaker System To Existing Computer Networks
- īస్ట్ Compatible With Cisco, Nortel, Avaya And Most IP Telephone Systems
- ï¿⅓ One-Way Paging
- � Web Interface For Control And Setup
- ï¿⅓ Can Operate Over Secure Networks
- آذِ½ Paging Prioritization
- ï¿⅓ Background Music
- � Web-based Firmware Upgradeable
- 17:1/2 Line Out Supports Amplified Speakers
- ï¿⅓ Wireless Option
- ï¿⅓ Synchronized Clock Option
- ï¿⅓ Full Supervision
- ï¿⅓ Wireless Option
- � Test / Setup Tones
- � Software Developer Kit Available
- 12.1/2 Compatible With Text/Audio To IP Telephones
- آزا Supports Syn-Apps, Checkmate, PagePro IP
- ï¿⅓ DHCP

Valcom VIP-120-IC SIP Celing Speaker Specifications Power

� External: 24 VDC @ 325 ma � POE: 802.3af, class 3

## Networking

- ï¿⅓ 10/100 Mbps Ethernet port
- ī¿½ Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup.
- 12.1/2 Time and date synchronization using SNTP



## Valcom VIP-120-IC One Way SIP Ceiling Speaker

## **Protocols**

- � IETF SIP (RFC3261)
- ï¿⅓ IETF IGMP version 3 (RFC3376)
- ï¿⅓ IETF RTP (RFC1889)
- ï¿⅓ IETF RFC2833
- ï¿⅓ Digest Authentication
- ï¿⅓ Dimensions and Weight
- ї¿½ Dimensions: 12.88" H x 12.88" W x 4" D (32.7 cm x 32.7 cm x 10.2 cm)
- ï¿1⁄2 Weight: 2.7 lbs (1.22 kg)

Price: £574.40