

Yealink T18P IP Phone (SIP-T18P)



Product Name: Yealink T18P IP Phone (SIP-T18P)

Manufacturer: -

Model Number: SIP-T18P

Yealink T18P IP Phone (SIP-T18P)

Please Note: The Yealink T18P has been discontinued. For an alternative, we recommended the Yealink T19P .

The Yealink T18P is an easy to use IP phone, coming equipped with a TI TITAN chipset that offers comprehensive telephony features including automatic provisioning, PoE, interoperability with leading IP-PBX and soft-switch developments. With a feature set that defies its price, the T18P is the intelligence purchase for reliable VoIP business performance.

Yealink T18P IP Phone (SIP-T18P) Features

- 1 VoIP account, Hotline
- Call waiting, Call transfer, Call forward
- Call hold, Mute, Redial, DND
- 3-way conferencing, Speed dial
- Direct IP call without SIP proxy
- Volume control, Ringtone selection
- Tone scheme, System log export
- Integrated Voice Response System

Designed for any working environment that requires a basic IP phone, the T18P is made for the desktop or is wall-mountable. The SIP-T18P is a cost-effective choice for small businesses, hotels, SoHo, college apartments and supermarkets.

Yealink T18P Technical Specifications

IP PBX System Integration

- Music on hold
- Call park, Call pickup
- Dial plan, Dial now
- Voicemail
- Message Waiting Indication (MWI)
- Distinctive ringtone

Voice Features

- Wideband codec: G.722
- Narrowband codec: G.711 /A, G.726,
- G.729AB, G.723.1
- VAD, CNG, PLC, AJB, AGC

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- NAT Traversal: STUN mode
- DTMF: In-band, out-of band (RFC2833) and SIP INFO
- Proxy mode and peer-to-peer SIP link mode
- IP Assignment: Static/DHCP
- TFTP/DHCP client
- Telnet/HTTP server
- DNS client

Yealink T18P IP Phone (SIP-T18P)

Management

- Built-in HTTP web server
- Configuration: browser/phone/auto-provision/IVR
- Auto provision via TFTP/FTP/HTTP/PnP
- Auto provision for firmware, configuration, ringtone etc

Security

- QoS: IEEE 802.1p/q tagging (VLAN), Layer 3ToS
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Admin/user configuration mode

Connectivity

Physical Features

- TI TITAN chipset
- 20 keys including 2 programmable keys
- 4 feature keys (Transfer/Hold/Mute/Redial)
- Phone label
- 1 x dual-color LED
- 1 x RJ45 10/100M Ethernet port
- Desktop with footstand (detachable),
- Wall-mountable
- Power adapter: AC 100~240V input and DC 5V/1.2A Output (Optional)
- Power over Ethernet
- (IEEE 802.3af class 1) optional
- Operating humidity: 10~95%
- Storage temperature: up to 60 C

Please Enquire

Options available for Yealink T18P IP Phone (SIP-T18P) :

Power Supply Required?

EU PSU required (+£3.99), UK PSU required (+£3.99), None - Using PoE.