

Yealink T18P IP Phone (SIP-T18P)



Product Name: Yealink T18P IP Phone (SIP-T18P)

Manufacturer: -

Model Number: SIP-T18P

Yealink T18P IP Phone (SIP-T18P)

Please Note: The Yealink T18P has been discontinued. For an alternative, we recommended the Yealink T19P.

The Yealink T18P is an easy to use IP phone, coming equipped with a TI TITAN chipset that offers comprehensive telephony features including automatic provisioning, PoE, interoperability with leading IP-PBX and soft-switch developments. With a feature set that defies its price, the T18P is the intelligence purchase for reliable VoIP business performance. Yealink T18P IP Phone (SIP-T18P) Features

ï¿1/2 1 VoIP account, Hotline

ï¿1/2 Call waiting, Call transfer, Call forward

� Call hold, Mute, Redial, DND

ï¿⅓ 3-way conferencing, Speed dial

� Direct IP call without SIP proxy

ï¿1/2 Volume control, Ringtone selection

� Tone scheme, System log export

� Integrated Voice Response System

Designed for any working environment that requires a basic IP phone, the T18P is made for the desktop or is wall-mountable. The SIP-T18P is a cost-effective choice for small businesses, hotels, SoHo, college apartments and supermarkets.

Yealink T18P Technical Specifications

IP PBX System Integration

ï¿1/2 Music on hold

� Call park, Call pickup

آزٰ½ Dial plan, Dial now

تز½ Voicemail

تز 1/2 Message Waiting Indication (MWI)

� Distinctive ringtone

Voice Features

ï¿1/2 Wideband codec: G.722

ï¿1/2 Narrowband codec: G.711 /A, G.726,

ï¿1/2 G.729AB, G.723.1

� VAD, CNG, PLC, AJB, AGC

Network Features

ï¿1/2 SIP v1 (RFC2543), v2 (RFC3261)

� NAT Traversal: STUN mode

12.1/2 DTMF: In-band, out-of band (RFC2833) and SIP INFO

12.1/2 Proxy mode and peer-to-peer SIP link mode

� IP Assignment: Static/DHCP

ï¿⅓ TFTP/DHCP client

� Telnet/HTTP server

ï¿⅓ DNS client



Yealink T18P IP Phone (SIP-T18P)

Management

- ïز½ Built-in HTTP web server
- تزار Configuration: browser/phone/auto-provision/IVR
- ï¿1/2 Auto provision via TFTP/FTP/HTTP/PnP
- าั¿½ Auto provision for firmware, configuration, ringtone etc

Security

- าั¿½ QoS: IEEE 802.1p/q tagging (VLAN), Layer 3ToS
- تزير Digest authentication using MD5/MD5-sess
- ï¿⅓ Secure configuration file via AES encryption
- � Admin/user configuration mode

Connectivity

Physical Features

- تان ۲۱ TITAN chipset
- � 20 keys including 2 programmable keys
- ï¿1/2 4 feature keys (Transfer/Hold/Mute/Redial)
- � Phone label
- � 1 x dual-color LED
- ï¿1/2 1 x RJ45 10/100M Ethernet port
- � Desktop with footstand (detachable),
- ï¿1/2 Wall-mountable
- تزاري Power adapter: AC 100~240V input and DC 5V/1.2A Output (Optional)
- ï¿⅓ Power over Ethernet
- ï¿⅓ (IEEE 802.3af class 1) optional
- � Operating humidity: 10~95%
- ï¿1/2 Storage temperature: up to 60 C

Please Enquire

Options available for Yealink T18P IP Phone (SIP-T18P):

Power Supply Required?

UK PSU required (+£3.99), EU PSU required (+£3.99), None - Using PoE.