

## Yealink USB-M3K USB Phone



Product Name: Yealink USB-M3K USB Phone

Manufacturer: -

Model Number: USB-M3K-R

Please Note: The Yealink USB-M3K USB Phone has been discontinued

### Yealink USB-M3K USB Phone

The Yealink USB-M3K is a small and light USB memory stick phone which allows you to bring softphone account information, contact list and chat history with you anywhere, working as both VoIP phone and memory disk. The pre-loaded softphone can auto-run on any PC without any additional installation once you plug the phone into the PC USB port. Real Plug and Play! Softphone and chat history saved on phone Real plug and play, ideal for travelling with VoIP. Yealink USB-M3K Key Features

• The pre-loaded softphone automatically runs under Windows 2000, XP or Vista 32bits/64bits

• Login information, contact list and chat history are stored automatically in the phone (this feature needs the softphone support)

• Independent storage memory available as portable memory drive (size: 128M/512M/1G or more)

• Sound card is built-in, no external power supply needed

• Stereo earphone is attached

### Yealink USB-M3K USB Phone - Technical Specifications

#### USB Audio Device

• Compatible with USB 1.1 and 2.0 Compatible with USB AUDIO DEVICE 1.0 Built-in sound card

#### Audio Features

• Support echo cancellation and full duplex communication 48K 16bits PCM format for playback Playback Capture(IN)

#### Playback

• Speaker impedance: 32Ohms +15

• 15% Frequency range: 20~20KHz

• Rated input power: 3mW

• Maximum input power: 10mW

#### Capture (IN)

• Microphone directivity: Omni directional

• Microphone sensitivity: -56dB +3dB@1Kz

• Impedance: Max: 2.2K @1KHz

• Frequency range: 20~20KHz S/N ratio: Min: 58dB@1KHz

#### Physical Features

• Dimension: 11mm x 21.5mm x 78mm

• Weight: 0.015kg

• LED: Yellow light indicating power on

## Yealink USB-M3K USB Phone

- One Headset jack
- Operation voltage: 4.5-5.5V
- Power consumption: Suspend mode<52mA; operating<110mA Operating Humidity: 10~95%
- Operating Temperature: 0 C~60 C

### Packing Details

- Unit Weight: 0.11kg
- Unit Dimension: 100 x 160 x 35 mm
- Qty: 50pcs
- N.W/CTN: 5.50kg
- G.W/CTN: 7.90kg
- Dimension: 585 x 405 x 205 mm
- Volume Weight: 8.11kg

### Softphone Security

The softphone will auto-run once plugged into PC, when disconnected, softphone can auto-logout All users' data and settings are encrypted, can not be viewed or modified in windows explorer

### System Requirements

Windows 2000 or XP or Vista 32bits and 64bits 400MHz processor and free USB1.1 or USB2.0 port Any broadband connection or minimum 33.6 Kbps dialup.

**Please Enquire**

---