

Sangoma D100-060E PCI Express Voice Transcoding Card (Up to 60 Transcoding Sessions)



Product Name: Sangoma D100-060E PCI Express Voice Transcoding Card (Up to 60 Transcoding Sessions)

Manufacturer: Sangoma

Model Number: D100-060E

Sangoma D100-060E PCI Express Voice Transcoding Card (Up to 60 Transcoding Sessions)

Please Note: This is a PCI Express Card. Please make sure your motherboard/server is compatible with this product.

[View PCI vs PCI-Express example](#)

IP telephony applications commonly require the use of multiple voice codecs, used to digitally compress voice signals and save on bandwidth. Voice signals from the Public Switched Telephone Network (PSTN) come in the form of the G.711 codec, but the VoIP terminal equipment and networks can support a variety of different voice codecs, such as G.729, G.726, AMR, G.722, iLBC, etc. Sangoma D100-060E Key Features

½ Support for Asterisk and FreeSWITCH

½ Media flows in and out of PCI or PCIe bus

½ Codecs supported: G.711, G.722, G.722.1, G.726, G.729AB, GSM-FR, GSM-EFR, AMR, AMR-WB (G.722.2), iLBC, L8 (Linear 8K), L16 (Linear 16K)

The VoIP infrastructure needs the capability to mediate between endpoints supporting different codecs, but this functionality requires digital signal processing tasks that are often costly and resource-intensive, and can affect the quality of the voice signals, if it introduces too much latency and delay. The D100 card, available in PCI and PCI Express form factors, converts simultaneous channels of transcoding from one type of codec (e.g. G.711) to another (e.g. G.729), without affecting latency or using up precious host CPU resources. The card allows up to 30, 60, 120, 240 or 400 channels of any-to-any voice codec conversion, with unmatched quality. All codecs are fully indemnified; no additional licensing is required for their use. The D100 works with both Asterisk® and FreeSWITCH™. With compatible drivers, these applications can use the D100 cards as seamless voice transcoding resources. Illustration

Sangoma D100-060E - Technical Specifications

Software

½ Support for Asterisk and FreeSWITCH

½ Media flows in and out of PCI or PCIe bus

½ Codecs supported: G.711, G.722, G.722.1, G.726, G.729AB, GSM-FR, GSM-EFR, AMR, AMR-WB (G.722.2), iLBC, L8 (Linear 8K), L16 (Linear 16K)

Power

½ PCI: 0.9 A @ 5 V (4.5 W)

½ PCIe: 1.35 A @ 3.3 V (4.5 W)

Dimensions

½ Compact factor for use in restricted chassis

½ Includes low profile bracket for installation in 2U chassis

½ PCI model: 121 mm x 63.5 mm

½ PCIe model: 94 mm x 63.5 mm

Sangoma D100-060E PCI Express Voice Transcoding Card (Up to 60 Transcoding Sessions)

Operating Systems

• Linux (all versions, releases and distributions from 1.0 up)

Certifications

• Emissions: FCC Part 15 Class A, CISPR 22, CISPR 24, EN 55022 (pending)

Temperature

• Temperature range: 0 – 50 °C

Production Quality

• ISO 9002

Warranty

• 30-day "no questions asked" return policy

• D-Series hardware comes with a standard 5-year warranty with product registration when purchased through an authorized Sangoma representative

Temperature

• Temperature range: 0 – 50 °C

Price: £650.60