

Snom MeetingPoint Extended Microphone



Product Name: Snom MeetingPoint Extended Microphone

Manufacturer: Snom

Model Number: MP-Mic

Please Note: This product has been discontinued. For an alternative, please see the other Snom VoIP Conference Phones.

snom MeetingPoint Conference Phone

The snom MeetingPoint Conference Phone is the perfect solution for anybody who makes frequent cross-location consultations. The snom MeetingPoint is the only SIP conference phone that allows you to use Microsoft Office Communication Server 2007 R2 and Standard SIP accounts in one conference phone.

snom MeetingPoint Key Features

- ½ Full duplex broadband sound technology
- ½ 3-way conference calls
- ½ Recording range up to 30 m²; room area or 10 participants
- ½ Simultaneous access to internal and external telephone books (LDAP)
- ½ Connection for add-on microphones for a larger recording range
- ½ Multiple SIP registrations

With the snom MeetingPoint, you are able to allow for a total of four parties to participate in the phone conference from different locations all over the world. This helps minimise time wasting and cuts costs. The snom MeetingPoint is perfect for use in medium to large conference rooms.

As result of the reliable suppression of disturbing background noise and its excellent sound quality you can hold your telephone conferences in large groups of up to 10 persons without affecting the intelligibility of the call.

snom MeetingPoint Conference Phone - Technical Specifications

General Information

- ½ Size: Diameter: 240 mm, Height: 77 mm
- ½ Display: Background-lit graphical LCD, 128x64 pixels
- ½ Weight: 1kg
- ½ Colour: black
- ½ Keypad: alphanumeric 0-9, *, #, dial, hang up, mute, increase volume, menu, conference, recording, volume control, 5 keys for navigation in the menu system
- ½ Microphone: circular (360°) recording characteristics
- ½ Reception range: up to 30 m²; < 10 persons
- ½ Speaker: Frequency range: 150-15000 Hz playback
- ½ Volume: 90 db SPI 0.5m. Equaliser function
- ½ Anti-theft protection: Kensington security slot

Connections

- ½ Network connection: 1xRJ-45
- ½ Power: PoE 10/100MBIT
- ½ External Power adapter 100-240 VAC/14 VDC
- ½ External microphones: modular 4/4 possible

Conditions

- ½ Temperature: 5°-40° Celcius
- ½ Air humidity: 20-80%

Snom MeetingPoint Extended Microphone

• Reverberation time: 0.5 S Rt 60
• Background noise: 45 dbA

Standards

• Telecom: TBR21, 47 CFR part 68/Tia, IC CS-03 Issue 1999/01/01
• EMC: EN301 489-1,3 EN300 220-1,2 FCC subpart B and C
• Electrical safety: UL 60950-1, EN 60950-1:200

Please Enquire
