

Alphatech IPDP Slim 1 button with camera (21IPC) VoIP Door Entry Panel



Product Name: Alphatech IPDP Slim 1 button with camera (21IPC) VoIP Door Entry Panel

Manufacturer: Alphatech

Model Number: 213203

Please Note: Alphatech products have a lead time of 1 - 2 weeks. Please call 0330 088 0195 and speak to our sales team who can confirm the current available stock for your requirements

Alphatech IPDP Slim 1 button with camera (21IPC) VoIP Door Entry Panel

The Alphatech IPDP Slim 1 button with camera (21IPC) Door Entry Panel receives power through the PoE (Power over Ethernet) technology. No additional cabling is necessary. If your Ethernet is not equipped with the PoE technology it is possible to use a PoE adaptor.

Slim IPDP - features

- Voice communication is supplied only from telephone line
- Two 25digit numbers (IP adress) with each button
- Day/night switching
- Possibility of the call extension by * or # choice
- Possible to connect two independent locks for door opening
- Possible use of 5 switch modes (e.g. camera, lighting, gradual opening)
- Two codes for hanging up the doorphone from telephone
- Two codes for door opening from telephone
- Six code locks (password from buttons at the door)
- Integrated heating of printed circuit
- Power supply 12V AC/DC, 500mA max or PoE technology
- White LED for automatic lighting for camera
- Permanent lighting through visiting cards
- Included color camera (autofocus)
- Ethernet – 10/100Mb with standard 10BaseT a 100BaseTx
- Web server for remote configuration – BOA
- Operating system – Linux 2.6
- SIP connection P2P or PBX network system
- WEB – firmware upgradeable
- WEB – interface for control and setup parameters
- Water protection - IP44

- Door Phone VoIP, compatible IPBX supporting SIP v2
- SIP proxy server mode to register your IP phones on the Door Phone
- IP Camera
- HTTP Management
- 2 Relays control
- CPL option
- VAD (Echo Cancellation)
- Day and night service
- Link pop up soft, video streaming and relays control from your PC

Technical DataParameters

- Operating Temperature: - 20° to + 50°C
- Dimensions (mm): >182*99*40

Alphatech IPDP Slim 1 button with camera (21IPC) VoIP Door Entry Panel

- PoE - power over ethernet
- Power Supply: 12Vss ± 2V , 10-12Vst ± 2V, Max. Consumption: 300mA at 12Vss
- Relays: Max. voltage of switch contact: 48V at I < 1A, Max. current of switch contact: 2A at U < 30 V

VoIP

- Signalisation : SIP v2
- Codecs Audio: G711u, G.711a, G726, GSM
- VAD (Echo Cancellation)
- Protocols : IP, TCP, UDP, HTTP, TELNET, SIP, RTP
- Management : web, telnet
- Interface : LAN 10/100 Base-Tx, Rj45
- Compatible : All SIP v2 IPBX. Valided on Cisco Call Manager, Alcatel OMNI PCX, Asterisk, Nexspan, Panasonic…

Price: £360.00
