

## OpenVox A800E44 8 Port Analog PCI Express card + 4 FXS + 4 FXO modules



Product Name: OpenVox A800E44 8 Port Analog PCI Express card + 4 FXS + 4 FXO modules

Manufacturer: -

Model Number: A800E44

Please Note: This product has been discontinued. Please see the OpenVox A810E PCI Express Asterisk Card for an alternative.

OpenVox A800E44 8 Port Analog PCI Express card + 4 FXS + 4 FXO modules

Please Note: This product may have a lead time of up to 1-2 weeks. Please call 0330 088 0195 and speak to our sales team who can confirm the current available stock for your requirement

Please Note: This is a PCI Express Card. Please make sure your motherboard/server is compatible with this product.

View PCI vs PCI-Express example

OpenVox A800E can be used for connecting analog telephones and analog POTS lines through a PC. It supports combinations of FXS and/or FXO modules for a total of 8 lines. The OpenVox A800E44 8 Port Analog PCI Express card + 4 FXS + 4 FXO modules delivers great voice quality in the telephony systems. With interchangeable FXS/FXO modules, it can eliminate the requirement for separate channel banks or access gateways. The A800E contains 8 module banks. Each bank supports one analog interface. The module banks may be filled with up to 8 FXO or FXS modules enabling the creation of any combination of ports. Scaling of an analog card solution is accomplished by simply adding additional cards. A800E works with Asterisk®, Elastix®, FreeSWITCH™, PBX in a Flash, trixbox®, Yate™ and IPPBX/IVR projects as well as other Open Source and proprietary PBX, Switch, IVR, and VoIP gateway applications.

Technical Specifications Feature Highlights

� Up to 8 Simultaneous PSTN Calls (Per PCle Slot)

า๊¿½ Interchangeable FXS and FXO modules

ī¿½ 3-Month "No Questions Asked" Return Policy

## **Target Applications**

� Channel Bank Replacement / Alternative

ï¿1/2 Small Office Home Office (SOHO) applications

17:1/2 Small and Medium Business (SMB) applications

ii. 1/2 Gateway Termination to analog telephones/lines

## Services and Features

� Caller ID and Call Waiting Caller ID

� ADSI Telephones

17:1/2 Loopstart Signaling Support

าั¿½ Up to 8 ports through a combination of FXS and FXO modules



ï¿1/2 8 RJ-11 interfaces on a single PCI bracket

� PCI Express 1.0,

า๊¿½ Firmware accelerate I/O access to achieve high stability

� Power: 7W Minimum, 37W Maximum

� Operation temperature: 0°C to 50 °C

� Storage temperature: -40°C to 125°C

ï¿1/2 Size: 24.8cm\*10.7cm\*1.8cm

ï¿⅓ Weight: 124g

**Operating Systems** 

าั¿½ Linux (all versions, releases and distributions from 1.0 up)

Minimum Hardware Requirement

ï¿1/2 800-Mhz Pentium III

ï¿⅓ 128MB RAM

ï¿1/2 Available PCI Express Slot

Standards Compliancy & Darranty

ï¿1/2 RoHS compliant

� Certificates: CE and FCC

ï¿1/2 Five Year Warranty!

Certified by trixbox CE and Elastix

Price: £343.80