

OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules



Product Name: OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules Manufacturer: -

Model Number: A800E80

Please Note: This product has been discontinued. Please see the OpenVox A810E PCI Express Asterisk Card for an alternative.

OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules

Please Note: This product may have a lead time of up to 1-2 weeks. Please call 0330 088 0195 and speak to our sales team who can confirm the current available stock for your requirement

Please Note: This is a PCI Express Card. Please make sure your motherboard/server is compatible with this product. View PCI vs PCI-Express example

OpenVox A800E can be used for connecting analog telephones and analog POTS lines through a PC. It supports combinations of FXS and/or FXO modules for a total of 8 lines. The OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules delivers great voice quality in the telephony systems. With interchangeable FXS/FXO modules, it can eliminate the requirement for separate channel banks or access gateways. The OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules contains 8 module banks. Each bank supports one analog interface. The module banks may be filled with up to 8 FXO or FXS modules enabling the creation of any combination of ports. Scaling of an analog card solution is accomplished by simply adding additional cards. A800E works with Asterisk®, Elastix®, FreeSWITCH™, PBX in a Flash, trixbox®, Yate™ and IPPBX/IVR projects as well as other Open Source and proprietary PBX, Switch, IVR, and VoIP gateway applications. Technical Specifications

� Up to 8 Simultaneous PSTN Calls (Per PCIe Slot)
� Interchangeable FXS and FXO modules
� 3-Month &Idquo;No Questions Asked" Return Policy

Target Applications

- ï¿¹/₂ Channel Bank Replacement / Alternative
- ï¿1/2 Small Office Home Office (SOHO) applications
- ï¿1/2 Small and Medium Business (SMB) applications
- ï¿1/2 Gateway Termination to analog telephones/lines

Services and Features

ï¿1/2 Caller ID and Call Waiting Caller ID

� ADSI Telephones

ï¿1/2 Loopstart Signaling Support

 \ddot{i}_{2} ^{1/2} Up to 8 ports through a combination of FXS and FXO modules



OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules

ï¿1/2 8 RJ-11 interfaces on a single PCI bracket

ï¿1/2 PCI Express 1.0,

ï¿1/2 Firmware accelerate I/O access to achieve high stability

ï¿1/2 Power: 7W Minimum, 37W Maximum

 $\ddot{\imath}_{\mathcal{E}} \overset{\prime_{2}}{\sim}$ Operation temperature: 0°C to 50 °C

ï¿1/2 Storage temperature: -40°C to 125°C

ï¿1/2 Size: 24.8cm*10.7cm*1.8cm

ï¿1/2 Weight: 124g

Operating Systems

i¿½ Linux (all versions, releases and distributions from 1.0 up)

Minimum Hardware Requirement

iزئ 800-Mhz Pentium III iزئ 128MB RAM iزئ Available PCI Express Slot

Standards Compliancy & amp; Warranty

i¿½ RoHS compliant i¿½ Certificates: CE and FCC i¿½ Five Year Warranty!

Certified by trixbox CE and Elastix

Price: £343.80