

## OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules



Product Name: OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules

Manufacturer: -

Model Number: A800E80

Please Note: This product has been discontinued. Please see the OpenVox A810E PCI Express Asterisk Card for an alternative.

OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules

Please Note: This product may have a lead time of up to 1-2 weeks. Please call 0330 088 0195 and speak to our sales team who can confirm the current available stock for your requirement

Please Note: This is a PCI Express Card. Please make sure your motherboard/server is compatible with this product.

[View PCI vs PCI-Express example](#)

OpenVox A800E can be used for connecting analog telephones and analog POTS lines through a PC. It supports combinations of FXS and/or FXO modules for a total of 8 lines. The OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules delivers great voice quality in the telephony systems. With interchangeable FXS/FXO modules, it can eliminate the requirement for separate channel banks or access gateways. The OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules contains 8 module banks. Each bank supports one analog interface. The module banks may be filled with up to 8 FXO or FXS modules enabling the creation of any combination of ports. Scaling of an analog card solution is accomplished by simply adding additional cards. A800E works with Asterisk<sup>®</sup>, Elastix<sup>®</sup>, FreeSWITCH<sup>®</sup>, PBX in a Flash, trixbox<sup>®</sup>, Yate<sup>®</sup>; and IPPBX/IVR projects as well as other Open Source and proprietary PBX, Switch, IVR, and VoIP gateway applications.

[Technical Specifications](#)

[Feature Highlights](#)

• Up to 8 Simultaneous PSTN Calls (Per PCIe Slot)

• Interchangeable FXS and FXO modules

• 3-Month "No Questions Asked" Return Policy

[Target Applications](#)

• Channel Bank Replacement / Alternative

• Small Office Home Office (SOHO) applications

• Small and Medium Business (SMB) applications

• Gateway Termination to analog telephones/lines

[Services and Features](#)

• Caller ID and Call Waiting Caller ID

• ADSI Telephones

• Loopstart Signaling Support

• Up to 8 ports through a combination of FXS and FXO modules

## OpenVox A800E80 8 Port Analog PCI Express card + 8 FXS modules

- 8 RJ-11 interfaces on a single PCI bracket
- PCI Express 1.0,
- Firmware accelerate I/O access to achieve high stability
- Power: 7W Minimum, 37W Maximum
- Operation temperature: 0&deg;C to 50 &deg;C
- Storage temperature: -40&deg;C to 125&deg;C
- Size: 24.8cm\*10.7cm\*1.8cm
- Weight: 124g

### Operating Systems

- Linux (all versions, releases and distributions from 1.0 up)

### Minimum Hardware Requirement

- 800-Mhz Pentium III
- 128MB RAM
- Available PCI Express Slot

### Standards Compliancy & Warranty

- RoHS compliant
- Certificates: CE and FCC
- Five Year Warranty!

Certified by trixbox CE and Elastix

**Price: £343.80**