

## Polycom CX3000 IP Conference Phone Microsoft Lync (OCS)



Product Name: Polycom CX3000 IP Conference Phone Microsoft Lync (OCS)

Manufacturer: -

Model Number: 2200-15810-025

Please Note: The Polycom CX3000 has been discontinued. For an alternatives, please see the Polycom range.

Polycom CX3000 IP Conference Phone Microsoft Lync (OCS)

The Polycom CX3000 IP Conference Phone delivers exceptional call performance. The CX3000 features Polycom HD Voice technology for crystal-clear calls, as well as being optimised for Microsoft's Lync Server 2010, creating a high-quality user experience with easy plug-and-play setup and configuration.

Polycom CX3000 Key Features

- IP conference phone optimised for Microsoft Lync
- Full Duplex technology
- HD Voice for clear, life-like conversations
- Expandable: 2 microphones can be added
- PoE

The Polycom CX3000 IP Conference Phone features embedded Microsoft Lync 2010 software, delivering a familiar user interface for conference call participants. The large high-resolution colour display and easy navigation buttons provide straightforward dialing controls, calendar and contact directory access, and presence indication.

Note: Please refer to the Polycom Lync VoIP Phone Range Detailed Comparison Table for more information.

Polycom CX3000 IP Conference Phone Technical Specifications

Audio - General

- Polycom HD Voice (Polycom Acoustic Clarity technology, mechanical design and wideband codec support)
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise fill
- DTMF tone generation/DTMF event RTP payload
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- Background noise suppression
- Cellular Phone Immunity
- Automatic gain control
- Dynamic noise reduction
- Acoustic echo cancellation

Audio - Speaker/Mic

- Speaker frequency response, 200 – 7kHz
- Speaker volume, maximum at 1/2 meter peak volume: 85dB
- Full-duplex speakerphone, compliant with IEEE 1329 Type 1
- Acoustic Echo Cancellation
- Mic frequency response: 150 - 7kHz
- Mic pickup: 3.5m (12 ft.)

## Polycom CX3000 IP Conference Phone Microsoft Lync (OCS)

### CODEC support

- Microsoft RTAudio
- G.722.1
- G.711 (narrowband, A-law and µ-law)

### User Interface

- Display, 3.5", QVGA TFT 24-bit colour graphical display, 320 x 240 pixels, with Unicode character capability
- LED backlight with adjustable brightness
- Backlight auto-dim when not in use

### Accessibility

- High contrast UI graphic screen option (software)
- Compatible with commercially-available TTY adapter equipment

### Buttons/keys

- 12-button dialpad, 0 - 9, \*, #
- Volume Up & Volume Down
- 2-way navigation: Up, Down, Select
- Home, Previous
- 2 soft keys + Menu
- On/Off Hook
- Mute/unmute button

### Indicators, LED

- Ringing/In Call/Mute/Hold indicator (x 3)
- Presence Indicator

### Connectivity

- Single Ethernet 10/100 Base-T with RJ45 connector port
- IEEE 802.3af class single PoE Ethernet 10/100 Base-T
- USB Device port, Type B female
- 2 extension Mic ports

### User Interface Languages

- English, French, Spanish, German, Italian, Dutch, Russian, Brazilian Portuguese, Japanese, Korean, Simplified Chinese, Traditional Chinese, Finnish, Swedish, Norwegian, Danish

### Software Features

- Pre-requisites: Microsoft Lync Server 2010, Microsoft Lync 2010
- Basic Mode: Contacts, Photos, Message waiting indicator, Standard Enterprise IP-PBX features, CAC, Survivability, E911 (US only), call park, etc., Teleworker support, Conference leader experience
- Enhanced Mode: Individual Voice Mail listings, Calendar, Join Conference, "Better Together", Lync integration call logs

## Polycom CX3000 IP Conference Phone Microsoft Lync (OCS)

### Power

- Built-in, auto-sensing IEEE 802.3af-2003 Power over Ethernet Class 3
- Optional AC power kit

### Physical

- Weight: 724g
- Dimensions (d x w x h): 365 x 324 x 67 mm
- Security cable lock slot

### Operating Conditions

- Temperature 0 to +40 degrees C (+32 to 104 degrees F)
- Relative Humidity: +10% to 90%, non-condensing
- Storage Temperature: -40 to +85 degrees C (-40 to +185 degrees F)

### Polycom CX3000 Ships With:

- Polycom CX3000 IP Conference Phone console
- 25ft Ethernet cable
- Captive USB cable
- Quickstart Guide
- Warranty Card

### Included Accessories

- Ethernet cable, 25 ft (7.5m)
- USB Cable, A to B (for "Better Together"), securable to device, 2m

### Accessories (available separately)

- AC Power Kit with 48V PSU, PoE Power Injector Cable and 2m line cord with local plug
- Extension mics, pair, with 3m (10ft.) cables

### Regulatory Certifications

- EMC – General: CISPR22
- EMC – USA (Class B): FCC Part 15
- EMC - Canada (Class B): ICES00.3: 1998
- EMC – EU (Class B): EN 55022, EN 55024
- EMC – ROW (Class B): C & A Tick (Australia), VCCI (Japan), GOST (Russia), KCC (Korea), TRA (UAE), Telepermit PTC220 (New Zealand)

### Electrical Safety Certifications

- UL60950-1 (USA / Canada)
- IEC / EN60950-1 (EU)
- GOST (Russia)
- KCC (Korea)

**Price: £559.10**