

## Spectralink 7622 DECT Handset



Product Name: Spectralink 7622 DECT Handset Manufacturer: -Model Number: 0264 0000

Please Note: This product has been discontinued.

Spectralink 7622 DECT Handset - Durable, application-enabled handsets for manufacturing The Spectralink 7622 combines durable design with elegant appearance and maximum functionality. The highly durable 7622 handset is dust tight and resistant to splashing water, vibrations, and shocks. This application-enabled handset is designed specifically for manufacturing and can be used even when wearing gloves.Spectralink 7622 DECT Handset Key Features

 $i_{\ell}$ <sup>1</sup>/<sub>2</sub> IP64-classified (dust tight and water splash proof)  $i_{\ell}$ <sup>1</sup>/<sub>2</sub> Alarm Key  $i_{\ell}$ <sup>1</sup>/<sub>2</sub> Headset jack with amplifier for industrial headsets

The Spectralink 7622 is ruggedised and durable in harsh conditions – no matter if they are humid, dusty, or dirty. The handsets combine maximum functionality, ease of use, and elegance with a durable design. And, the handsets are designed to meet the needs of a mobile workforce in industrial and manufacturing environments.

Spectralink 7622 Handset Technical Specifications Approvals EMC:

� EN 301 489-1 � EN 301 489-6 � Radio: EN 301 406 � Safety: EN 60950-1

Size and Weight

ï¿1/2 Size: 148 x 50.4 x 21.6 mm ï¿1/2 Weight: 123 g. incl. battery ± 10 g.

Speech / Standby Time

i¿<sup>1</sup>/<sub>2</sub> Spectralink 7622: i¿<sup>1</sup>/<sub>2</sub> Speech time: up to 23 (27 hours in economy mode) i¿<sup>1</sup>/<sub>2</sub> Standby time: up to 118 hours

#### Battery

ï¿1/2 Battery: Li-ion battery

� Easily removable battery with option to use in shift-operation environments � Battery lifetime under proper charge and dischargeconditions: Two years or 500 charging cycles



# Spectralink 7622 DECT Handset

#### Temperature

� Operating temperature: -10º - 55º C (14º F - 131º F) � Charging temperature: 0º - 40º C (32º - 104º F)

**IP** Rating

ï¿1/2 According to EN60529:IP64 classified (dust tight and water splash proof)

Tests

ï¿1/2 Drop test: IEC 60068-2-31

### **Please Enquire**

Options available for Spectralink 7622 DECT Handset :

#### Spectralink Charger for 72 and 76 Series

Required (+£13.00), Not Required.

**Spectralink UK PSU for Charger** Required (+£13.90), Not Required.

**Spectralink Dual Charger & slot for spare battery** Required (+£54.00), Not Required.