

Spectralink 7722 DECT Handset



Product Name: Spectralink 7722 DECT Handset

Manufacturer: -

Model Number: 0266 0000

Please Note: This product is end of life. For an alternative, please see the other Spectralink phones.

Spectralink 7722 DECT Handset - The Ultimate Wireless Solution for Healthcare Personnel The Spectralink 7722 handset is a robust and application-enabled handset designed especially for healthcare. The handsets are dust protected and resistant to splashing water, vibrations and shocks. The Spectralink 7722 handset is disinfectant-resistant and has a membrane keypad for easy cleaning to avoid the spread of bacteria. Spectralink 7722 Key Features

12/2 Large colour icons with customisable text messaging

i¿½ IP64-classified (dust tight and water splash proof)

� Disinfectant resistant and membrane keypad

The Spectralink 7722 is integrated with third-party applications, such as nurse call or equipment monitoring system, the alarm button and alarm icons allow immediate reaction in emergency situations. The Ultimate Wireless Solution for Healthcare PersonnelSpecial healthcare alarm icons have been developed for the Spectralink 7722, which ensures that messages and alarms are easy, fast, and intuitive to understand.

Benefits

T¿½ Improved reaction time to medical emergencies via alarms in case of heart attack, epileptic attack, and other situations where lives are at stake

า๊¿½ More time to patient care and faster interaction between patient and caregiver

า๊¿½ Resistance to disinfectants and easy clean keypad membrane reduce the risk of spreading bacteria and diseases

آذِ½ Automatic alarms - if man down, no movement, or running is detected - increase personal safety

าั¿½ Tear-off string and alarm button increase safety for personnel in high-risk environments

آذِ½ Protection against splashing water enables caretakers to assist patients in wet rooms without detaching the handset

Spectralink 7722 Technical Specification Approvals

12.1/2 Dual switched auto-sensing 10/100 Mbps Ethernet ports

� Integrated PoE

Size and Weight

� Size: 148 x 50.4 x 21.6 mm (5.8 x 2.0 x 0.8 in.) � Weight: 115 g incl. battery (4.0 oz incl. battery)

Speech / Standby Time

าั¿½ Spectralink 7722: – Speech time: up to 23 (27 hours in economy mode)– Standby time: up to 118 hours

Battery



Spectralink 7722 DECT Handset

ï¿⅓ Battery: Li-ion battery

ī సైస్ట్ Easily removable battery option to use in shift operationenvironments

า๊¿½ Battery lifetime under proper charge and dischargeconditions: Two years or 500 charging cycles

Temperature

� Operating temperature: -10º - 55º C (14º - 131º F) � Charging temperature: 0º - 40º C (32º - 104º F)

IP Rating

ī¿1/2 According to EN60529: – IP 64 classified (dust tight and water splash proof)

Tests

ï¿1/2 • Drop test: IEC 60068-2-32

Please Enquire

Options available for Spectralink 7722 DECT Handset:

Spectralink UK PSU for Charger

Not Required, Required (+\$18.78).

Spectralink Charger for 77 Series

Not Required, Required (+\$18.78).

Spectralink Dual Charger & slot for spare battery

Not Required, Required (+\$73.76).