

Yealink T32G IP Phone (SIP-T32G)



Product Name: Yealink T32G IP Phone (SIP-T32G)

Manufacturer: -

Model Number: SIP-T32G

Yealink T32G IP Phone (SIP-T32G)

Please Note: The Yealink T32G has been discontinued. For an alternative, we recommend the Yealink T41P .

The Yealink T32G is a VoIP phone that is perfectly suited to managers who have a demanding set of communication needs. The T32G features a 3" TFT-LCD, 400 x 240 pixel, 262K colour screen, 3 VoIP accounts and HD Voice.

Yealink SIP-T32G IP Phone Key Features

- Dual-port Gigabit Ethernet, Power over Ethernet
- 3" TFT-LCD, 262K colors, Intuitive user interface
- TI Aries chipset and TI voice engine
- HD Voice: HD Codec, HD speaker, HD handset
- 3 VoIP accounts, BLF/BLA, IPv6
- Headset, Wall mountable

3 Lines

The Yealink T32G supports up to 3 VoIP lines, each with a standalone configuration.

HD Voice Quality

Supporting advanced wideband voice codec G.722 and full-duplex hands-free speakerphone with enhanced AEC, the T32G IP Phone delivers superior voice clarity.

Executive Level Phone

Yealink's T32G VoIP Phone offers 32 keys including 3 soft keys, BLF / BLA, XML screen, which increase working efficiency.

High-Resolution Display Screen

The T32G IP Phone offers a 3" TFT-LCD, 400 x 240 pixel screen with 262K colors that gives the user an ultra-clear display.

Note: Please refer to the Yealink VoIP Phone Range Detailed Comparison Table for more information.

Yealink T32G Technical Specifications

Phone Features

- 3 VoIP accounts, Hotline, Emergency call
- Call hold, Call waiting, Call forward, Call return
- Call transfer (Blind/Semi-attended/Attended)
- Caller ID display, Redial, Mute, DND
- Auto-answer, 3-way conferencing
- Speed dial, SMS, Voicemail
- Message Waiting Indication (MWI) LED
- Tone scheme, Volume control
- Direct IP call without SIP proxy
- Ring tone selection/Import/Delete
- Phonebook (1000 entries), Black list
- Call history: Dialed/Received/Missed/Forwarded
- Menu-driven user interface

Yealink T32G IP Phone (SIP-T32G)

- Localized language and input method
- 3 Soft keys programmable

Advanced Features

- XML phonebook search/import
- LDAP phonebook
- XML Idle Screen
- Action URL & Active URI
- Wallpaper, Screensaver
- Color Picture Caller-ID
- Theme, Screen Sleep

IP PBX System Integration

- Busy lamp field (BLF), BLF list, (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold
- Call park, Call pickup
- Call recording, Call completion
- Group listening, Group pickup
- Anonymous call, Anonymous call rejection
- Network conference
- Distinctive ringtone
- Dial Plan, Dial-now

Codecs and Voice Features

- Wideband codec: G.722
- Narrowband codec: G.711 & /A, G.723.1
- G.726, G.729AB
- VAD, CNG, AEC, PLC, AJB, AGC
- Full-duplex speakerphone with AEC

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- IPv6
- DNS SRV (RFC3263)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info
- Proxy mode and peer-to-peer SIP link mode
- IP Assignment: Static/DHCP/PPPoE
- Bridge/router mode for PC port
- TFTP/DHCP/PPPoE client
- Telnet/HTTP/HTTPS server
- DNS client, NAT/DHCP server
- Logout

Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- Auto-provision with PnP
- SNMP V1/2 optional, TR069 optional

Yealink T32G IP Phone (SIP-T32G)

• Configuration: browser/phone/auto-provision
• Factory configuration customized
• Trace package and system log export

Security

• Open VPN, 802.1x, VLAN QoS (802.1pq), LLDP
• Transport Layer Security (TLS)
• HTTPS (server/client), SRTP (RFC3711)
• Digest authentication using MD5/MD5-sess
• Secure configuration file via AES encryption
• Phone lock for personal privacy protection
• Admin/VAR/User 3-level configuration mode

Connectivity

Physical Features

• 2 x RJ45 10/100/1000Mbps Ethernet ports
• TI Aries chipset
• 3" TFT-LCD, 400 x 240 pixel, 262K colors
• 32 keys including 3 programmable keys
• 5 LEDs: 1 x power, 3 x line, 1 x message
• Wall-mountable
• 1 x RJ9 (4P4C) handset port
• 1 x RJ9 (4P4C) headset port
• Power adapter: AC 100~240V input and DC 5V/2A output (Optional)
• Power over Ethernet (IEEE 802.3af)
• Power consumption: 4.0W
• Net weight: 0.77kg
• Dimension: 185 x 200 x 90mm
• Operating humidity: 10~95%
• Storage temperature: up to 60°C

Yealink T32G Certifications

Please Enquire

Options available for Yealink T32G IP Phone (SIP-T32G) :

Power Supply Required?

UK PSU required (+£3.99), EU PSU required (+£3.99), None - Using PoE.

RPS Extension ID

TEXT.

RPS Extension Password

TEXT.

RPS Display Name

Yealink T32G IP Phone (SIP-T32G)

TEXT.

RPS PBX URL

TEXT.

RPS NAT Enabled

TEXT.

RPS Outbound Proxy

TEXT.

RPS SIP Port

TEXT.

RPS Enable Outbound Proxy

RPS Own Server URL

RPS Own Server Name