

AudioCodes MediaPack 114 Analog VoIP Gateway 4 Port FXC (MP114/4O/SIP)



Product Name: AudioCodes MediaPack 114 Analog VoIP Gateway 4 Port FXO (MP114/4O/SIP)

Manufacturer: AudioCodes
Model Number: MP114/40/SIP

AudioCodes MediaPack 114 Analog VoIP Gateway 4 Port FXO (MP114/4O/SIP)
The AudioCodes MP114/4O/SIP is an analog VoIP Gateway which is a cost-effective, best-of-breed technology product. These stand-alone analog VoIP Gateways provide superior voice technology for connecting legacy telephones, fax machines and PBX systems with IP-based telephony networks, as well as for integration with IP PBX systems.

AudioCodes MP114/4O/SIP Key Features

ï¿1/2 4 analog ports

� T.38 fax compliant

ï¿⅓ 3-way conference with local mixing

� Call pickup

Hunt groups

� Call forwarding

� Call hold

ï¿1/2 Call transfer

T¿½ Advanced telephony features such as long-haul, metering tones generation, country dependent MWI and Caller ID for true integration with the existing telephony infrastructure

AudioCodes MP114/4O/SIP Technical Specifications Interfaces

� Analog Signaling: 4 ports, FXS, FXO loop-start � Network Interface: 10/100 BASE-T, RJ-45

Media Capabilities

ī¿½ Voice Coders: G.711 (A-law and µ-law), G.723.1, G.726, G.727, G.729A/B, G.722 เ๋¿½ VoIP Features: G.168-2004 echo cancellation, silence detection and comfort noise generation, dynamic programmable jitter buffer

រ៉េះ $^{\prime\prime}$ Call Progress Tones: Programmable detection and generation tones, pre-recorded tones generation

ī¿½ DTMF: In-band and out-of-band signaling, RFC 2833, SIP INFO/NOTIFY

ī¿½ Fax Over IP: Group 3/super G3 fax over IP, T.38 relay, automatic switching to G.711

IP Networking and Telephony Protocols

ï¿1/2 VLAN: 802.1 p/Q VLAN tagging

آذِ 1/2 IP Transport: IPV4/IPV6*, DiffServ, TOS

ī సై Control Protocols: SIP (RFC 3261) over UDP, TCP and TLS (1.2)

� Media Protocols: RTP (RFC 3550), SRTP (RFC 3711), RTCP (RFC 3550), RTCP-XR (RFC 3611)

Management Protocols

T¿½ OAM&P:- Web GUI, SSH/Telnet, SNMP v2/v3, INI file- AudioCodes' One Voice Operation Center- User authentication and access control via RADIUS
T¿½ Automatic Configuration:- Zero-touch provisioning- Configuration/firmware download via HTTP(s), FTP and TFTP- DHCP-based provisioning - options 66, 67 and 160- VLAN ID discovery



AudioCodes MediaPack 114 Analog VoIP Gateway 4 Port FXC (MP114/4O/SIP)

using LLDP

آزا Voice Menu: Basic configuration using standard touch-tone phone (MP-11x only)

Survivability During Network Failure

ī¿½ PSTN Fallback: PSTN fallback upon power failure, IP connection failure, customer-defined IP QoS thresholds (MP-114 and MP-118)

ī సైస్ట్ Survivability: Stand Alone Survivability (SAS) for 25 SIP users

Analog Telephony Features

12/2 3-Way Conference: On-board 3-way conference

ī¿½ MWI: Message Waiting Indication: High (neon) and low (LED) voltage, FSK, stutter dial tone ī¿½ Caller ID: Bellcore GR-30-CORE Type 1 using Bell 202 FSK modulation, ETSI Type 1, NTT,

Denmark, India, Brazil, United Kingdom and DTMF ETSI CID (ETS 300-659-1)

īస్ట్ Polarity Reversal/Wink: Immediate or smooth to prevent erroneous ringing

ī స్ట్రి Metering Tones: 12/16 KHz sinusoidal bursts, generation on FXS

ī¿½ Distinctive Ringing: By frequency (15-100 Hz) and cadence patterns

Subscriber Line Interface

រី¿½ Ring Voltage: Sine: 54 VRMS typical (balanced ringing only)

ï¿1/2 Ring Frequency: 25-100Hz

ï¿1/2 Maximum Ringer Load: REN3

ī¿½ Loop Impedance: Up to 1,500 ohm for the MP-11x, up to 1,600 ohm for the MP-124

(including phone impedance)

ï¿1/2 Line Current: Up to 32 MA on 4 ports

Physical

ï¿1/2 Power: 100-240 V AC/50-60 Hz

ī¿½ Environmental: - Operational: 5 to 40°C (41 to 104°F)- Storage: -25 to 85°C

(-13 to 185°F)- Humidity: 10 to 90% non-condensing

� Dimensions: 42x172x220 mm

īస్ట్ Mounting: Table top, wall mount, rack mount (with an optional shelf)

� Weight: MP-1xx: 0.5 kg (1.1 lbs.) approx.

Price: £349.40