

## Redfone foneBRIDGE2 Quad T1/E1 Ethernet Bridge



Product Name: Redfone foneBRIDGE2 Quad T1/E1 Ethernet Bridge

Manufacturer: RedFone Communications

Model Number: 750-5000

The foneBRIDGE2 Quad is a 4 Port E1/T1 Ethernet Bridge Asterisk PBX T1/E1 Redundancy, High Availability & Load Balancing in an economical Enterprise class solution foneBRIDGE2 is a T1/E1 PRI-to-Ethernet Bridge. It is an integrated black-box "appliance" designed to streamline installation and enable redundant design of Asterisk based VoIP systems.

foneBRIDGE2 eliminates the need to install proprietary TDM hard-ware cards in approved/compatible server configurations. Instead, foneBRIDGE2 terminates T1/E1 PRI lines on the trunk side and provides direct Ethernet communication to a network of Asterisk servers using native Asterisk TDMoE formats and utilities.

Engineered around our unique high-speed SoC (System-on-Chip) TDMoE engine, foneBRIDGE2 provides low-latency delivery of your critical voice traffic Enables T1/E1 Load Balancing Share trunk resources among multiple Asterisk servers through the load balancing capabilities of foneBRIDGE2 Failover & Asterisk HA Enabled High-Availability through rapid failover capabilities ensures your critical telephony services are always on and available Flexible Configuration Configurable on a per-port basis, foneBRIDGE2 allows you to mix multiple telephony standards on a single deployment Solid State Embedded Appliance

- No moving components
- Low heat and power consumption
- High MTBF (mean time before failure)

### Target Applications

- T1/E1 PRI Trunk termination
- Legacy PBX-to-Asterisk integration
- High-Availability/Failover Asterisk clusters
- Channel Bank connectivity
- Mixed telephony environments (ex. E1 PRIs + T1 Channel Banks)

### Standards

#### Telephony

- PRI Switch Compatibility- EuroISDN, AT&T 4ESS, DMS 100, Lu-cent 5E, NI1/NI2; Network or CPE
- Line Interface- Dual or Quad T1/E1 (RJ45), per port configur-able
- Line Encoding- AMI/B8ZS for T1, AMI/HDB3 for E1
- Super Frame (SF) and Extended Super Frame (ESF)
- Robbed Bit Signaling (RBS/CAS)

#### Ethernet

- 10/100-BASE-TX Half/Full-duplex
- 2 x Dedicated RJ45

### Specifications

- Electrical: DC 500mA Max @ 5V (2.5W)
- Environmental: 0 to 50 deg C operating
- Physical: Dimensions: 5.00" x 6.50" x 1.00" Weight: 1 pound Mounting: Flange Mount or

## Redfone foneBRIDGE2 Quad T1/E1 Ethernet Bridge

Desktop

**Price: Â£1,219.00**

---