

**Dinstar DWG2004 SIP, GSM VoIP Gateway - 4 Channels  
(DWG2000-4G)**

## Dinstar DWG2004 SIP, GSM VoIP Gateway - 4 Channels (DWG2000-4G)



Product Name: Dinstar DWG2004 SIP, GSM VoIP Gateway - 4 Channels (DWG2000-4G)

Manufacturer: -

Model Number: DWG2000-4G

Please Note: The Dinstar DWG2004 SIP GSM Gateway has been discontinued and been replaced by the Dinstar DWG2000C-4GSM VoIP Gateway

Dinstar DWG2004 SIP, GSM VoIP Gateway - 4 Channel (DWG2000-4G)

The Dinstar DWG2004 is a Quad-band SIP/GSM gateway that supports 4 GSM channels / SIM cards. The DWG2004 works with Asterisk® based IP PBXs like Elastix®, trixbox®, and AsteriskNOW®, as well as other Open Source and proprietary SIP based IP PBXs, Switch, IVR, and VoIP gateway applications.

½ Dinstar DWG2004 SIP/GSM gateway with 4 GSM channels

½ Applications: SIP IP PBX GSM Trunk, SIP VoIP line Gateway, SMS Server

½ Quad-Band GSM 850/900/1800/1900 MHz

### Specification

½ Dimensions (Length\*Width\*Height, unit: mm): 113\*77.5\*24.5

½ Weight (unit: kg): 1.6

½ Operating temperature (unit: C): 0-40

½ Storage temperature (unit: C): -20-70

½ Operating humidity: 10%-90%

½ GSM/CDMA/WCDMA SIM Ports: 1 channel

½ Power input: 220VAC/50Hz/0.2A

½ External power input: 12VDC/1A

½ Power (unit: W): 4w

½ Network interface: 10/100BASE-TX

½ Number of WAN ports: 1

½ Number of LAN ports: 1

**Please Enquire**