Created on: Friday 29 March, 2024

# CyberData VoIP V3 Paging Server (011146)



Product Name: CyberData VoIP V3 Paging Server (011146)
Manufacturer: CyberData
Model Number: 011146

CyberData VoIP V3 Paging Server 011146
The CyberData SIP Paging Server enables users, through a single SIP phone extension, to access multiple zones for paging with bell scheduling in a VoIP network and to connect to legacy analog overhead paging systems.
Key Features

ï¿½ Bell Scheduler with up to 25 “bells”
ï¿½ PoE 802.3af enabled (Power-over-Ethernet)
ï¿½ 19-inch Rack mount option
ï¿½ Remote amp fault sensor
ï¿½ SIP RFC 3261 compatible
ï¿½ Multicast output
ï¿½ Two SIP endpoints (one for Night Ringer)
ï¿½ DTMF control of zone selection
ï¿½ Delayed page support
ï¿½ User uploadable audio files

A second SIP endpoint can be configured as a night ringer playing a user-uploadable audio file.
Other Features

ï¿½ Line-In connection for music-on-hold multicasting
ï¿½ Line-out connection to support analogue Amps
ï¿½ Web-based configuration and firmware upload
ï¿½ Supports 600 Ohm output
ï¿½ Page start relay contacts
ï¿½ Page directly to Polycom phones

The easy-to-use, web-based configuration provides a graphical user interface to set up to 100 paging zones with unique multicast address and port number combinations.
The device connects via a single cable to a standard PoE 802.3af compliant switch.

CyberData VoIP V3 Paging Server 011146 Technical Specifications

ï¿½ Bell Scheduler for alerts for mass notification
ï¿½ Protocol: SIP RFC 3261 Compatible
ï¿½ Ethernet I/F: 10/100 Mbps
ï¿½ Power Input: PoE 802.3af or 48VDCSpecifications
ï¿½ Dimensions: 6.11”L x 4.05”W x 1.15”H
ï¿½ Warranty: 2 years limited
ï¿½ Boxed Weight: 1.8 lbs.
ï¿½ Payload Types: G711
ï¿½ Operating Temperature: -30 to 55 C (-22 to 131 F)
ï¿½ Regulatory Compliance: FCC Class A, UL 60950
ï¿½ Page Port Output: Balanced 600 Ohm 10VPP
ï¿½ Line In: Input Signal Amplitudes 2.0 VPP maximum, Input Impedance  10k Ohm
ï¿½ Line Out: Output Signal Amplitudes 2.0 VPP maximum, Output Level  +2dBm nominal, Total Harmonic Distortion 0.5% maximum, Output Impedance  10k Ohm

# CyberData VoIP V3 Paging Server (011146)

**Price: £535.70**