

Sangoma Vega 60G Gateway 2 BRI



Product Name: Sangoma Vega 60G Gateway 2 BRI

Manufacturer: Sangoma

Model Number: VEGA-60G-02BRI

Sangoma Vega 60G Gateway 2 BRI

The Sangoma Vega 60G 2 BRI Media Gateway is designed to simplify the integration of Basic Rate ISDN (BRI) devices to a VoIP network. Each BRI interface can be independently configured as network side or terminal side. The Vega 60G 2 BRI Media Gateway can, therefore, be used for IP PBX connectivity to PSTN and SIP trunking offerings.

Sangoma Vega 60G 2 BRI Gateway Key Features

- ½ 2 BRI Ports
- ½ Flexible Call Routing
- ½ Emergency Backup with Enhanced Network Proxy
- ½ Interoperability with a Wide Range of Legacy & IP Equipment
- ½ Voice, FA, and Modem Support
- ½ Automated Configuration with TR-069

Sangoma Vega 60G 2 BRI - Technical Specifications

VoIP Interfaces

- ½ SIP V1, V2
- ½ Fax support – up to G3 FAX, T.38
- ½ Modem support – up to V.90, G.711
- ½ Audio Codecs: G.711 (a-law/μ-law), G.729a (8kbps), G.723.1 (5.3/6.4 kbps), G.726, T.38

Telephony Interfaces

- ½ 2x S/T interfaces presented on RJ-45
- ½ Point to point or point to multipoint
- ½ Each interface configured NT or TE High precision clock optional

LAN Interfaces

- ½ 1x RJ-45 Gigabit Ethernet 1000BaseT / 100BaseTx / 10BaseT, full / half duplex
- ½ PoE option available on some models
- ½ Dual LAN port option available

Telephony Features

- ½ Call waiting
- ½ Call forward – unconditional, busy, no-answer
- ½ Call transfer – blind, consultative 3-way conference
- ½ Do not disturb
- ½ Message waiting indicator – audible, visual
- ½ Music on hold
- ½ Executive barge
- ½ Caller ID presentation & screening
- ½ SIP registration & digest authentication

Operations, Maintenance & Billing

Sangoma Vega 60G Gateway 2 BRI

- HTTP(S) web server
- RADIUS accounting & login
- Remote firmware upgrade
- Auto configuration upgrade
- SNMP V1, V2 & V3
- Syslog
- TR-069 / TFTP / FTP support
- VT100 – RS232 / Telnet / SSH
- Voice readback of IP parameters

Routing & Numbering

- Direct Dialing In (DDI)
- SIP registration to multiple proxies
- Dial planner – sophisticated call routing capabilities, standalone or gatekeeper / proxy integration

Call Quality

- Adaptive jitter removal
- Silence suppression
- Type of Service (ToS)
- Differentiated Services (DiffServ)
- Comfort noise generation
- 802.1p / Q VLAN tagging
- QoS statistics reporting
- Echo cancellation (G.168 up to 128ms tail)

Security & Encryption

- Media – SRTP
- SIP – TLS
- Management – HTTPS, SSH Telnet
- Configurable user login passwords

Certification

- EMC (Class B): EN55022, EN55024, FCC Part 15, AS/NZS3548, VCCI
- Safety: EN60950, IEC60950, UL60950, AS/NZS60950

Environmental

- 0°C .. 40°C
- 0% .. 90% humidity (non-condensing)

LED Indicators

- LAN: speed / activity

Physical Dimensions

- 1U: 200 x 127 x 43mm (WxDxH)
- Weight: .8kgs (1.7lbs)

Sangoma Vega 60G Gateway 2 BRI

Power

↳ Standard product: External 12V 24W AC/DC adapter

Price: £429.50

Options available for Sangoma Vega 60G Gateway 2 BRI :

Peace of Mind Packages

[Not Required](#), [Gold \(+£127.27\)](#), [Platinum \(+£190.91\)](#).