

## 2N IP Safety - 1 button & 10W speaker (9152101W)



Product Name: 2N IP Safety - 1 button & 10W speaker (9152101W)

Manufacturer: 2N Telecommunications

Model Number: 9152101W

**Please Note:** All 2N products come with a 3 year warranty as standard however, this can be extended up to 5 years. Customers have the option to extend their warranty by either one or two years. To find out more, please [click here](#) or call our sales team on 0330 088 0195.

**Please Note:** The 2N Helios Intercoms may require additional licenses to activate all features.

### 2N IP Safety - 1 button & 10W speaker (9152101W)

The 2N IP Safety 1 button + 10W speaker is a modern emergency intercom that will ensure two-way communication between two remote locations when needed. Its reliability is enhanced by robust construction and other practical properties that take into account its use in high-stress operations. Its striking orange colour and illuminated button ensure that it is visible and functions even in crisis situations.

- ½ The greatest durability on the market
- ½ A striking orange colour
- ½ Illuminated emergency button
- ½ High-quality audio, 10W D-Class amplifier
- ½ Ease of use and remote administration
- ½ External source / PoE power supply

In communication, this intercom uses the standard SIP protocol, so that compatibility with third-party products is guaranteed. It is resistant to external influences and boasts the highest coverage class pursuant to the IPX (IP69) standard. The high-powered 10W speaker, 2 integrated microphones and intelligent echo suppression guarantee high-quality and comprehensible two-way communication even in noisy environments, such as industrial operations or transport infrastructure. Communication is initiated by pushing its single, freely programmable button, which is visibly illuminated in blue.

### 2N IP Safety - 1 button Technical Specifications

#### Power supply

- ½ 802.3af (PoE) 48 V / 380 mA DC or
- ½ Adaptor 230 V10%, 50/60 Hz / 12V DCDC power supply 12 V / 1A DC

#### VoIP

- ½ Signalization SIP
- ½ Number of voice channels 2
- ½ Audio Codecs G.711, G.729

#### Audio

- ½ Audio 2 integrated microphones, 10W D-Class amplifier, Full duplex (AEC)

#### Interfaces

- ½ Ethernet Connector RJ-45, Ethernet speed 10/100 BASE-T
- ½ Reley outputs Maximal voltage 30 V DC, Maximal current 1 A DC

## 2N IP Safety - 1 button & 10W speaker (9152101W)

### Other

- Dimensions ,217x109x83 mm (h&times;w&times;d)
- Weight max. 2000 g
- Operating temperatures from &ndash;40 to +55 &ordm;C
- Cover level IP65, IP69

**Price: £893.90**

---