

2N IP Safety - 1 button & 10W speaker (9152101W)



Product Name: 2N IP Safety - 1 button & 10W speaker (9152101W)

Manufacturer: 2N Telecommunications

Model Number: 9152101W

Please Note: All 2N products come with a 3 year warranty as standard however, this can be extended up to 5 years. Customers have the option to extend their warranty by either one or two years. To find out more, please [click here](#) or call our sales team on 0330 088 0195.

Please Note: The 2N Helios Intercoms may require additional licenses to activate all features.

2N IP Safety - 1 button & 10W speaker (9152101W)

The 2N IP Safety 1 button + 10W speaker is a modern emergency intercom that will ensure two-way communication between two remote locations when needed. Its reliability is enhanced by robust construction and other practical properties that take into account its use in high-stress operations. Its striking orange colour and illuminated button ensure that it is visible and functions even in crisis situations.

- ✓ The greatest durability on the market
- ✓ A striking orange colour
- ✓ Illuminated emergency button
- ✓ High-quality audio, 10W D-Class amplifier
- ✓ Ease of use and remote administration
- ✓ External source / PoE power supply

In communication, this intercom uses the standard SIP protocol, so that compatibility with third-party products is guaranteed. It is resistant to external influences and boasts the highest coverage class pursuant to the IPX (IP69) standard. The high-powered 10W speaker, 2 integrated microphones and intelligent echo suppression guarantee high-quality and comprehensible two-way communication even in noisy environments, such as industrial operations or transport infrastructure. Communication is initiated by pushing its single, freely programmable button, which is visibly illuminated in blue.

2N IP Safety - 1 button Technical Specifications

Power supply

- ✓ 802.3af (PoE) 48 V / 380 mA DC or
- ✓ Adaptor 230 V10%, 50/60 Hz / 12V DCDC power supply 12 V / 1A DC

VoIP

- ✓ Signalization SIP
- ✓ Number of voice channels 2
- ✓ Audio Codecs G.711, G.729

Audio

- ✓ Audio 2 integrated microphones, 10W D-Class amplifier, Full duplex (AEC)

Interfaces

- ✓ Ethernet Connector RJ-45, Ethernet speed 10/100 BASE-T
- ✓ Relay outputs Maximal voltage 30 V DC, Maximal current 1 A DC

2N IP Safety - 1 button & 10W speaker (9152101W)

Other

½ Dimensions ,217x109x83 mm (h×w×d)

½ Weight max. 2000 g

½ Operating temperatures from –40 to +55 ºC

½ Cover level IP65, IP69

Price: £788.70
