

Openvox V100-BOX-256 (Up to 256 transcoding Sessions)



Product Name: Openvox V100-BOX-256 (Up to 256 transcoding Sessions)

Manufacturer: -

Model Number: V100-BOX-256

Please Note: This product has been discontinued. For an alternative, please see our other Asterisk Software.

Openvox V100-BOX Up to 256 transcoding Sessions, Enclosure V100-BOX-256

The Openvox V100-BOX-256 is an integrated box designed to streamline installation. With an external Power Supply, it can work alone by using an Ethernet port and also be stacked up to 5 instances on a 19 inch rack mount. The V100-BOX from Openvox can be worked with Asterisk® and FreeSWITCH®.

Feature

- High density up to 256 transcoding Sessions
- No additional License Fee
- Relieve Host CPU Load
- Release API for Integration
- OS : Linux and Windows
- Integrates in Asterisk® and FreeSWITCH®
- Support distributed or integrated Application

Openvox V100-BOX-256 - Technical Specifications

Codec Support

- G.711
- GSM-FR

- G.722
- GSM-EFR

- G.722.1
- AMR

- G.726
- AMR-WB (G.722.2)

- G.729AB
- iLBC

* Except for AMR and AMR-WB
Target Applications

- Hosted VoIP GateWay
- Conferencing Server

Openvox V100-BOX-256 (Up to 256 transcoding Sessions)

• 1/2 IVR Server
• 1/2 Distributed Office PBX
• 1/2 Call Centers

Dimensions

• 1/2 131x67.5x31mm

Interface

• 1/2 10/100/1000 BASE-T RJ45

Power Requirments

• 1/2 0.6A @12V

Operating Temperature Range

• 1/2 0 – 50 °C

Humidity

• 1/2 10 TO 90% NON-CONDENSING

Hardware And Software Requirement

• 1/2 Windows/Linux in Host

Certifications

• 1/2 FCC Part 15B，EN55022 Class B，EN55024 EN60950 (Pending)

Warranty

• 1/2 5-year warranty

Related Accessories

The OpenVox V100-Bracket is a 1U & 19” bracket, designed for rackmounting installation of up to 5 instances of V100-BOX.

Please Enquire

Options available for Openvox V100-BOX-256 (Up to 256 transcoding Sessions) :

V100-Bracket Required?

Openvox V100-BOX-256 (Up to 256 transcoding Sessions)

[Not Required](#), [Required \(+£35.00\)](#).