

Openvox V100-BOX-256 (Up to 256 transcoding Sessions)



Product Name: Openvox V100-BOX-256 (Up to 256 transcoding Sessions)

Manufacturer: -

Model Number: V100-BOX-256

Please Note: This product has been discontinued. For an alternative, please our other Asterisk Software.

Openvox V100-BOX Up to 256 transcoding Sessions, Enclosure V100-BOX-256

The Openvox V100-BOX-256 is an integrated box designed to streamline installation, With an extern Power Supply, it can work alone by using Ethernet port and also being stacked up to 5 instances on a 19 inch rack mount. The V100-BOX from Openvox can be worked with Asterisk® and FreeSWITCH®;

Feature

- High density up to 256 transcoding Sessions
- No addionnal License Fee;
- Relieve Host CPU Load
- Release API for Integration
- OS : Linux and Windows
- Integrates in Asterisk® and FreeSWITCH®;
- Support distributed or intergrated Application

Openvox V100-BOX-256 - Technical Specifications

Codec Support

• G.711
• GSM-FR

• G.722
• GSM-EFR

• G.722.1
• AMR

• G.726
• AMR-WB (G.722.2)

• G.729AB
• iLBC

* Except for AMR and AMR-WB
Target Applications

• Hosted VoIP GateWay
• Conferencing Server

Openvox V100-BOX-256 (Up to 256 transcoding Sessions)

• IVR Server
• Distributed Office PBX
• Call Centers

Dimensions

• 131x67.5x31mm

Interface

• 10/100/1000 BASE-T RJ45

Power Requirements

• 0.6A @12V

Operating Temperature Range

• 0 – 50 °C

Humidity

• 10 TO 90% NON-CONDENSING

Hardware And Software Requirement

• Windows/Linux in Host

Certifications

• FCC Part 15B，EN55022 Class B，EN55024 EN60950 (Pending)

Warranty

• 5-year warranty

Related Accessories

The OpenVox V100-Bracket is a 1U & 19” bracket, designed for rackmounting installation of up to 5 instances of V100-BOX.

Please Enquire

Options available for Openvox V100-BOX-256 (Up to 256 transcoding Sessions) :

V100-Bracket Required?

Openvox V100-BOX-256 (Up to 256 transcoding Sessions)

Required (+£35.00), Not Required.