

## OpenVox V100-PTMC-064 Transcoding Card (Up to 64 transcoding Sessions)



Product Name: OpenVox V100-PTMC-064 Transcoding Card (Up to 64 transcoding Sessions)

Manufacturer: -

Model Number: V100-PTMC-064

Please Note: This product has been discontinued. For an alternative, please our other Asterisk Software.

OpenVox V100-PTMC Up to 64 transcoding Sessions,PMC V100-PTMC-064

The OpenVox V100-PTMC-064 new generation transcoding series delivers 3 models for different types of applications.

- ½ Up to 64 transcoding sessions
- ½ No Licensing Fees\*
- ½ PMC / Enclosure / Extending Evaluation Board / Ethernet card
- ½ Reduce Host CPU Load
- ½ Flexible Adaptability
- ½ Provides RJ45 media/control flow paths.
- ½ Works with Asterisk® and FreeSWITCH®;

### Overview

Because of its low bandwidth requirements, the voice data compression codecs, such as G.729, G.726, AMR, G.722, iLBC, etc., are commonly used in VoIP applications.

The V100-PTMC-064 from OpenVox is a PMC for transcoding. In addition, it is a PTMC for extending PMC to support stand telecom and telephony interfaces. It is usable with a wide range of PCC, PT2CC, PT3CC, PT5CC and can provide CompactPCI/fornt-panel Gbe/Backplane Gbe/Local CT media/control flow paths. These features can save the cost and support flexible applications.

The V100-PTMC-064 can be worked with Asterisk® and FreeSWITCH®. In addition, the media message-based API makes the development easy since the messages and media flow communicate between the PCC's host and V100-PTMC-064 through Ethernet interface .

### OpenVox V100-PTMC-064 - Technical Specifications

#### General Features

- ½ No addionnal License Fee#65297;
- ½ Compliant with PICMG 2.15(PTMC) electrical specification and IEEE 1386, IEEE1386.1(PMC)mechanical specifications
- ½ Configurable for PT2MC/PT3MC/ PT5MC
- ½ Local CT Bus allowing flexible routing of TDM timeslots both between the PTMC Sites and the H.110 backplane CT Bus.
- ½ PT5MC includes Gbe connectivity to backplane resources
- ½ PMC/PT2MC/PT3MC include Gbe connectivity to front panel
- ½ Multi Media/Control Flow Paths
- ½ Relieve Host CPU Load
- ½ Release API for Integration
- ½ OS : Linux and Windows
- ½ Integrates in Asterisk® and FreeSWITCH®;
- ½ Support distributed or intergrated Application

#### Codec Support

## OpenVox V100-PTMC-064 Transcoding Card (Up to 64 transcoding Sessions)

- G.711
- GSM-FR

- G.722
- GSM-EFR

- G.722.1
- AMR

- G.726
- AMR-WB (G.722.2)

- G.729AB
- iLBC

Except for AMR and AMR-WB  
Target Applications

- Hosted VoIP GateWay
- Conferencing Server
- IVR Server
- Distributed Office PBX
- Call Centers

### Dimensions

- Compliant with IEEE1386 mechanical specifications
- 149.0x74.0mm (PCB)

### Interface

- PCI :32bit 33/66MHz
- Local CT
- 10/100/1000 BASE-T RJ45
- UART
- Backplane Gbe
- PMC Connector

### Power Requirements

2.2A @3.3V

### Operating Temperature Range

0 &ndash; 50 &deg;C

### Humidity

10 TO 90% NON-CONDENSING

### Hardware And Software Requirement

## OpenVox V100-PTMC-064 Transcoding Card (Up to 64 transcoding Sessions)

• PCC,PT2CC,PT3CC,PT5CC  
• Windows/Linux in Host

The V100-PTCC is a PMC for transcoding. In addition, it is a PTMC for extending PMC to support stand telecom and telephony interfaces. It is usable with a wide range of PCC, PT2CC, PT3CC, PT5CC and can provide CompactPCI/fornt-panel Gbe/Backplane Gbe/Local CT media/control flow paths. These features can save the cost and support flexible applications.

### Please Enquire

---

Options available for OpenVox V100-PTMC-064 Transcoding Card (Up to 64 transcoding Sessions) :

#### Openvox VC100-PTCC

Required (+£360.00), Not Required.