

Panasonic KX-UDS124 Wideband 4 channel DECT Cell Station



Product Name: Panasonic KX-UDS124 Wideband 4 channel DECT Cell Station

Manufacturer: Panasonic
Model Number: KX-UDS124UK

Panasonic KX-UDS124 Wideband 4 channel DECT Cell Station

The Panasonic KX-UDS124 is certified for use with Digium Asterisk and Broadsoft Broadworks. The KX-UDS124 offers high-quality business communications with up to 32 Cell Stations and High Definition Audio (G.722).PanasonicKS-UDS124 DECT Cell Station Key Features

- īస్ట్ KX-UDS124 4 Channel " Multi-Cell" Wideband Cell Station
- īస్ట్ Designed for use with Broadsoft Broadworks, Asterisk and SwitchVox systems
- า๊¿½ High Definition &Idquo;HD" Audio (G.722) for excellent voice quality (KX-UDS124 only)
- าั¿½ Enhanced voice processing for superior voice quality in poor signal conditions
- ï¿⅓ Web interface setup for easy remote configuration
- � Power Over Ethernet support
- ī¿½ Up to 32 Cell Stations can be grouped with seamless handover
- تز½ 'Over the air' firmware upgrades
- า๊¿½ No additional hardware or server required

The Panasonic sip based dect telephony system range is built with a SIP server independent architecture, for wide ranging compatibility. Note: Please refer to the Multicell DECT Detailed Comparison Table for more information.

Panasonic KX-UDT124 Wideband 4 channel DECT Cell Station Specification Features

- ï¿1/2 Max Simultaneous calls 4 calls
- ï¿1/2 Max handsets Up to 255
- � Max no. of Cell Stations 128 total; per air sync group
- آذًا Network Interfaces 10baseT/100baseTX auto MDI/MDI-X Ethernet LAN port
- าั¿½ Power Source Power over Ethernet (IEEE802.3af) class 1
- ï¿1/2 AC Adapter (KX-A239) optional
- � Operating Conditions 0C 40C

Configuration

- � Embedded Web Server
- ï¿⅓ Password protected admin access

Business Features (requires SIP server support)

- ï¿1/2 Network based conference
- � Call Forward / DND sync
- � Connected Line ID presentation
- � Direct Inward Dialling (DID)
- � Direct Dialling in (DDI)

Network Configuration

- � DHCP / Static IP address
- � DNS (Primary / Secondary)
- าั¿½ SNTP Simple network time protocol

Time and Date Handling



Panasonic KX-UDS124 Wideband 4 channel DECT Cell Station

� Clock

� Call Timer

� Daylight savings time support

Quality of Service

� DSCP

ï¿⅓ Static VLAN

ï¿⅓ ToS

Voice Quality

� Adaptive Jitter Buffer

� Configurable Packetization Period

Features

� Codec Support

� G.722

ï¿⅓ G.711 (ulaw, alaw)

� G.729a

� G.726

� Configurable codec preferences

ï¿1/2 Adjustable Codec frame size

Customisable Tone Generation

ï¿⅓ Dial Tone

ï¿⅓ Ringing Tone

ï¿⅓ Busy Tone

ï¿⅓ Reorder Tone

ï¿⅓ Stutter Tone

Management and Provisioning

ï¿⅓ Web browser configuration

ï¿1/2 Status and stats display

រ៉េ $^{\prime\prime}$ Remote firmware upgrade HTTP, HTTPS, TFTP, FTP

� 'Over the air' software upgrade

า๊¿½ Remote configuration file download HTTP, HTTPS, TFTP, FTP

161/2 Auto provisioning Via Panasonic Redirect Server

� Broadsoft Device Management System

� TR-069 for remote management

� Pre-provisioning by DHCP Opt.66

آزِ½ Dial plan

ï¿⅓ Online CS monitor

Security

ï¿⅓ Encrypted configuration files

ï¿⅓ MD5 authentication

� HTTPS Server authentication

ï¿⅓ DECT encryption



Panasonic KX-UDS124 Wideband 4 channel DECT Cell Station

Price: £257.20