

2N Helios IP Force - 2 buttons (9151102R)



Product Name: 2N Helios IP Force - 2 buttons (9151102R)

Manufacturer: -

Model Number: 9151102R

Please Note: This product has been discontinued. We recommend the 2N Helios IP Force - 2 Button 9151102RW as an alternative.

2N Helios IP Force - 2 buttons - 9151102R

The 2N Helios IP Force 9151102R is an exceptionally sturdy IP intercom featuring 1 call button and a 10W internal speaker. This will ensure you effortless communication with the people coming to your door, in combination with reliable security for your building entrance. 2N Helios IP Force 9151101W Key Features

- � IP connected Door Intercom
- าั¿½ Robust construction and high protection rating for outdoor & mp; high impact / risk applications
- � 2 Buttons / 2 Name Labels
- า๊ะ่½ Proximity Card Reader (for use with 2N Proximity Card or Key Fob)
- ï¿⅓ SIP communication protocol
- آذًا Integrates within a LAN, WAN, Web Ethernet network system
- 12.1/2 Power over Ethernet (PoE) (or 12v power supply)
- � Integrated web server for configuration
- � iPad, iPhone, Smart Phone, Tablet support
- آزري Web Interface Administration / Control of all 2N Helios IP devices from one location
- าั¿½ Stylish, discreet design; robust materials and construction
- า๊ะใน IP65 protection rating for weatherproof conditions

The 2N Helios IP Force units are exceptionally tough and resilient with IP65 certification. This means they are perfect for high risk areas that require vandal proof intercoms. 2N IP Force units are commonly used in public access areas, prisons, flats and apartment blocks, hospitals, universities, government offices, car parks and more.

Technical Specifications

Features:

- $\ddot{\imath}$ SIP communication protocol
- � Works in the Ethernet network
- � Power supply over ethernet
- تز½ PoE (12Vpower adapter optional if necessary)
- ï¿⅓ Integrated web server for configuration
- ï¿1/2 10W speakers
- i¿½ RFID Card Reader support (only model "ready for card reader")
- تزير Video without Videophone support, software IP Eye
- ï¿⅓ iPad, iPhone, Smartphones support
- 17.1/2 Web administration of all intercoms from one place
- 161/2 Integrated scheduler with day/night/weekend modes
- 12.1/2 Can be used as a standard VoIP telephone and a code
- � lock (keypad equipped models)
- � Up to 999 users / user groups (with professional version)
- ï¿1/2 Water resistant IP 69



2N Helios IP Force - 2 buttons (9151102R)

- ï¿1/2 Electronic lock switch
- ï¿1/2 controlled directly from the VoIP telephone

Technical specification:

- ï¿⅓ Signalization protocol:
- ï¿1/2 Signalization protocol SIP 2.0 (RFC-3261)

Audio:

- ï¿⅓ Microphone 2 integrated microphones
- ï¿⅓ Amplifier 10W D-Class amplifier
- � Loudspeaker 1W (optionaly 10W)
- ï¿1/2 Full duplex Yes (AEC)
- ϊ¿½ Protocols RTP/RTSP
- ï¿1/2 Codecs G.711, G.729

Mechanical:

- Ϊ¿½ Operating temperature range -4 °F 131 °F
- ï¿1/2 Storage temperature range -40 °F 158 °F
- � Relative humidity 10% 95% (not condensing)
- � Dimensions 8,54" x 4,29" x 3,27"
- $\ddot{\imath}$ ۇ½ 9,53" x 5,35" x 3,27" with frame
- � Protection level: IP65, selected models IP69

Price: £754.90