

Beronet Telephony Appliance with integrated Berofix for 16 channels BNTA16



Product Name: Beronet Telephony Appliance with integrated Berofix for 16 channels BNTA16

Manufacturer: -

Model Number: BNTA16

Beronet IP PBX Telephony Appliance with integrated Berofix for 16 channels BNTA16

The Beronet Telephony Appliance with integrated Berofix for 16 channels BNTA16 is the ideal hardware platform for customers and integrators, looking for an integrated and reliable computer solution, where the berofix Gateways are already fully integrated.

- ï¿½ No moving parts, long-life and reliable
- ï¿½ 100% Aluminium construction, Robust, Lightweight and Rust-Free
- ï¿½ There is a module for every Scenario – PRI, BRI, Hybrid, Analog & GSM
- ï¿½ Install any Operating System on the same Appliance
- ï¿½ PCM connector extends the Appliance with an extra beroNet Gateway
- ï¿½ Remotely manage and monitor connectivity through beroNet Cloud
- ï¿½ Operational use of under 24W saving €200 per year in electricity
- ï¿½ Silent & can be placed anywhere in any office
- ï¿½ GSM ready for Least Cost Routing & Mobile PBX
- ï¿½ SkypeConnect™ integrates Skype into the PBX installation

Please view the BeroNet Berofix LineInterface Modules [here](#).

The elegant design of beroNet BNTA16 delivers superior energy efficient properties, which is very important in telephony systems that are used in 24/7 operation. With a power consumption of less than 24W during normal operation. The beroNet Telephony Appliance is designed for telephony applications in the SOHO and SME markets and can address businesses with up to 50 users. The customer can choose his favorite telephony software. The beroNet Telephony Appliance is tested with Linux and Windows operating systems and is compatible with the following software solutions:

Technical Specifications

Hardware:

- ï¿½ Intel Atom N2800 2x1,86Ghz
- ï¿½ 2GB RAM
- ï¿½ 30 GB SSD
- ï¿½ 4 x external USB 2.0, Gigabit Ethernet port
- ï¿½ Keyboard and Monitor Support
- ï¿½ Silent system and Fanless design

Telephony:

- ï¿½ up to 16 /64 concurrent channels and two module slots for up to two of the following modules:
- ï¿½ BF4S0 4 ISDN BRI Ports
- ï¿½ BF2S02FXS 2 ISDN BRI and 2 analog FXS ports
- ï¿½ BF1E1 1 ISDN PRI /E1 ports
- ï¿½ BF2E1 2 ISDN PRI/E1 ports
- ï¿½ BF4FXO 4 analog FXO ports
- ï¿½ BF4FXS 4 analog FXS ports
- ï¿½ BF2GSM 2 GSM ports

Dimensions and Weight:

Beronet Telephony Appliance with integrated Berofix for 16 channels BNTA16

• Dimensions: 35 x 25,5 x 4,6 cm (1U industry standard rack- or wallmountable chassis, 19" wide; Brackets optional)

• Weight: 2 kg (depending on module configuration)

• Power supply: 12V DC 3A Desktop, Voltage: 110/230V 50/60Hz

Environment:

• Storage conditions: Temp: -20°C to 70°C

• Working conditions: Temp: 0°C to 40°C / Humidity: 20% - 95%, non condensing

Warranty and Service:

• 24 months beroNet Warranty

• "Bring In Service" (standard)

• optional available "Advanced Exchange Service"

Price: £632.40
