

Netgear Prosafe FS728TP 24-Port 10/100 Smart Switch with 4 Gigabit Ports and 24 POE Ports



Product Name: Netgear Prosafe FS728TP 24-Port 10/100 Smart Switch with 4 Gigabit Ports and 24 POE Ports
Manufacturer: -
Model Number: FS728TP

Please Note: This product has been discontinued. Please see the Netgear GS728TPv2 ProSAFE 24-Port Gigabit PoE Smart Switch.

Netgear Prosafe FS728TP 24-Port 10/100 Smart Switch with 4 Gigabit Ports and 24 POE Ports
The Netgear Prosafe 24-Port 10/100 Smart Switch provides power and data using built-in IEEE 802.3af PoE on all 24 ports. In addition, the Prosafe 24-Port 10/100 Smart Switch offers an intuitive Web-based management tool for quick and easy deployment and configuration making it ideal for deploying access points, VoIP phones and IP-based surveillance cameras.
Netgear Prosafe 24-Port 10/100 Smart Switch with 4 Gigabit Ports and 24 POE Ports Features

- Full 24 10/100 Smart Switch with 24 PoE Ports
- Four gigabit ports for high speed connections
- Easy-to-manage web-based GUI

This Netgear Prosafe FS728TP is equipped with highly advanced features such as access control lists (ACL), 802.1x port authentication, enhanced QoS, rate limiting and IGMP snooping among others to provide a small and medium-sized business with a network that is geared for growth while providing scalability and reliability. With the utility of 24 10/100 Mbps ports, four copper 10/100/1000 Mbps ports and two combination (copper/hot-swappable small form-factor pluggable (SFP)) Gigabit ports for optional fiber connectivity, growing business networks, classrooms and workgroups can benefit from superior performance and keep up with expanding network needs. This high-performing switch features a non-blocking wire-speed architecture with an 12.8 Gbps switching capacity for maximum data throughput. All 28 RJ-45 ports automatically negotiate to the highest speed and support Auto Uplink™ technology to make the right link.

Full-featured, Flexible Power over Ethernet (PoE)

With a total power budget of 192 Watts, customers can choose to plug in up to 24 Ethernet or Fast Ethernet devices and mix in up to 24 802.3af IP-based devices. Power-over-Ethernet (PoE), optimizes the installation and power management of network devices such as wireless access points (AP), Voice over IP (VoIP) phones, and IP-based surveillance cameras.

Power-over-Ethernet (IEEE 802.3af) capabilities reduce installation time and costs for many new network productivity devices. Free your wireless AP deployments and IP cameras from the restrictions of power outlet proximity using a standard Cat 5 UTP cable. Enable uninterrupted power supply for all your PoE devices by powering your switch from a UPS device.

Advanced Security

These switches also provide advanced features that provide more robust security to the SMBs. These include:

- 802.1x for authentication
- ACL filtering to permit or deny traffic based on MAC and IP addresses.

Advanced Quality of Service

Priority queuing ensures high-priority traffic gets delivered efficiently, even during congestion from high traffic bursts. Companies implementing network telephony or video conferencing, for example, need to be able to prioritize such voice and video traffic and other real-time applications over less latency-sensitive traffic to ensure reliability and quality. The ability to prioritize traffic ensures quality of latency-sensitive services and applications despite increasing traffic loads. The ProSafe FS728TP provides several advanced QoS features:

Netgear Prosafe FS728TP 24-Port 10/100 Smart Switch with 4 Gigabit Ports and 24 POE Ports

- 802.1p based prioritization
- Layer 3-based (DSCP) prioritization
- Rate limiting

"Smart" Management Features

Manage all ProSafe Smart Switches as from an easy-to-use Web console that can be used to configure all features, as well as monitor and trouble-shoot. These switches also have SNMP (v1, 2c and 3) to collect and track data to monitor the network health, as well as manage devices, and more easily enforce critical IT controls and policies. SNMP v2c is most commonly deployed, as it provides better reporting capabilities than SNMP v1. Companies interested in more robust security may opt for SNMP v3, which provides data encryption.

All ProSafe Smart Switches provide world-class reliability with a Lifetime Warranty and optional ProSupport Maintenance Packages. These switches are optimized for ProSafe Network Management Software (NMS200) and works with other SNMP-based management software.

Netgear Prosafe FS728TP - Technical Specifications Network Protocol and Standards Compatibility

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-X
- IEEE 802.3x full-duplex flow control
- IEEE 802.3af (Power over Ethernet)

Power Supply

- Power consumption: 256W maximum
- 100-240VAC/50-60-Hz universal input
- PoE budget: 192W

Network Ports

- 24 10/100 Mbps auto sensing Fast Ethernet
- 4 10/100/1000 Mbps auto-sensing Gigabit Ethernet switching ports (RJ-45)
- 2 Dual Personality SFP slots

Physical Specifications

- Dimensions: (w x d x h) 440 x 257 x 43 mm (17.3 x 10.1 x 1.7 in)
- Weight: 3.57 kg (7.86 lb)

Electromagnetic Emissions

- CE EN 55022, EN 61000 and EN 55024
- FCC Part 15 Class A
- VCCI Class A
- C-Tick
- KCC
- CCC

Environmental Specifications

Netgear Prosafe FS728TP 24-Port 10/100 Smart Switch with 4 Gigabit Ports and 24 POE Ports

- Operating temperature: 32° to 122° F (0° to 50° C)
- Storage temperature: -4° to 158° F (-20° to 70° C)
- Operating humidity: 90% maximum relative humidity, non-condensing
- Storage humidity: 95% maximum relative humidity, non-condensing
- Operating altitude: 10,000 ft(3,000 m) maximum
- Storage altitude: 10,000 ft (3,000 m) maximum

LEDs

- Per port (10/100 and Gigabit): Link/activity, speed
- Per device: Power, Fan
- Per PoE port: PoE Power, PoE fault

Safety

- UL/cUL 60950
- CE EN 60950
- CCC
- CB

System Requirements

- Category 5 UTP Network cables or above
- Network card for each PC
- Network software (e.g., Windows®)
- Web browser (e.g., Internet Explorer 6.0 or higher, Netscape 6.0 or higher)

Administrative Switch Management

- IEEE 802.1Q static VLAN (128 groups, static)
- IEEE 802.1p Class of Service (CoS)
- Port-based QoS
- DSCP-based QoS
- DiffServ
- IEEE802.3ad link aggregation (manual or LACP)
- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- IEEE 802.1ab Link Layer Discovery Protocol (LLDP)
- LLDP-MED
- SNMP v1, v2c, v3
- RFC 1213 MIB II
- RFC 1643 Ethernet interface MIB
- RFC 1493 bridge MIB
- RMON group 1, 2, 3, 9
- RFC 2131 DHCP client
- Auto voice VLAN
- DHCP Filtering
- Auto denial-of-service (DoS) protection
- HTTP and HTTPS
- Ping and traceroute
- Power saving when link down

Netgear Prosafe FS728TP 24-Port 10/100 Smart Switch with 4 Gigabit Ports and 24 POE Ports

- IEEE 802.1x
- Port-based security by locked MAC addresses
- IP and MAC ACL
- Storm control for broadcast, multicast and unknown unicast packets
- IGMP snooping v1/v2
- Protected Port
- PoE Timer
- Port-based ingress and egress rate limiting
- SNMP
- Port mirroring support (many to one)
- Web-based configuration
- Configuration backup/restore
- Password access control
- RADIUS Support
- TACACS+ support
- Syslog
- Firmware upgradeable
- Cable test

Performance Specifications

- Forwarding modes: Store-and-forward
- Bandwidth: 12.8 Gbps
- Network latency: μ s for 64-byte frames in store-and-forward mode for 100 Mbps to 100 Mbps transmission
- Buffer memory: 1 MBytes per system
- Address database size: 4,000 media access control (MAC) addresses per system
- Addressing: 48-bit MAC address
- Mean time between failures (MTBF): 237,497 hours (~27 years)
- Acoustic noise: 38.1 dBA

Modules

- AGM731F 1000BASE-SX SFP Module
- AGM732F 1000BASE-LX SFP Module
- AGM733 1000BASE-ZX SFP Module

Warranty and Support

- ProSafe Lifetime Warranty†;
- ProSupport 24x7 Advanced Technical Support, 1 year (included)*

Package Contents

- 24-port PoE Smart Switch with Gigabit Ports (FS728TP)
- Rubber footpads
- Power cord
- Rack-mount kit
- Resource CD
- Installation guide

Netgear Prosafe FS728TP 24-Port 10/100 Smart Switch with 4 Gigabit Ports and 24 POE Ports

Price: Â£194.60
