

Grandstream GXP1165 IP Phone



Product Name: Grandstream GXP1165 IP Phone

Manufacturer: -

Model Number: GXP1165

Please Note: The Grandstream GXP1165 has been discontinued. For an alternative, we recommend the Grandstream GXP1610.

Grandstream GXP1165 IP Phone 1-Line IP Phone With LCD Display

The Grandstream GXP1165 is a next generation IP phone that is designed for small to medium sized businesses. The GXP1165 features a single SIP account, up to 2 call appearances, a 128x40 graphical LCD, 3 XML programmable context-sensitive soft keys, dual network ports with intergrated PoE, 3 – way conference and Electronic Hook Switch (EHS) with Plantronics headsets.

Grandstream GXP1165 Key Features

ï¿1/2 128x40 graphical LCD

17.1/2 Single SIP account, up to 2 call appearances

ï¿1/2 3 XML programmable context-sensitive soft keys

រ៉េ្យ Phonebook with up to 500 contacts and call history up to 200 records

T¿½ Automated personal information service (e.g., local weather), personalised music ring tone/ring back tone

ī¿½ Dual switched auto-sensing 10/100Mbps network ports, intergrated PoE

Ti. S for advanced accurity pretention, 803 by for madia access central

TLS for advanced security protection, 802.1x for media access control

The Grandstream GXP1165 also deliveries superior audio quality, rich and leading telephony features such as personalised information, customisable application service, automated provisioning for easy deployment, advanced security protection for privacy and broad interoperability with most 3rd party SIP devices and leading SIP/NGN/IMS platforms. The GXP1165 is a perfect choice for small-to-medium businesses looking for a high quality feature rich VoIP Phone at an affordable cost.

Grandstream GXP1165 Technical Specification

Protocols/Standards

� SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP,PPPoE, TFTP, NTP, STUN, SIMPLE, TR-069, 802.1X IPv6

Network Interfaces

2∕′; آ

Dual Switched 10/100Mbps ports, intergrated PoE (GXP1165 only)

Graphical Display

ï¿1/2 128x40 graphical LCD display

Feature Keys

12/5٪

1 SIP account, 3 XML programmable context sensitive keys, 5 navigational/menu/ volume keys, 9 dedicated functions keys for Phonebook, Message (with LED indicator), Hold, Transfer, Conference, Flash, Speakrphone, Volume, Send, Redial,



Grandstream GXP1165 IP Phone

Voice Codecs

� Support for G.723.1, G.729A/B, G.711 μ/a, G.726-32, G.722 (wide-band), iLBC, in-band and out-of-band DTMF (in audio, RFD2833, SIP INFO)

Telephiny Features

ī¿½ Hold, Transfer, Forward, 3-way conference, downloadable phone book, (XML, LDAP, up to 500 items), call waiting, call log (up to 200 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalised music ringtones, server redundancy and fail-over

Headset Jack

រី¿½ RJ9, supporting Electronic Hook Switch (EHS) with Plantronics headsets

Base Stand

ï¿1/2 Yes, 1 angle position available

Wall Mountable

� Yes

QoS

ï*:1*/2

Layer 2 (802.1q, 802.1p) and layer 3 (ToS, DiffServ, MPLS) QoS

Security

آذِا User and administrator level passwords, MD5 and MD5-sess based authentication, AES encrypted configuration file, SRTP, TLS, 802.1x media access control

Multi-Language

½'ۃ

English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese, etc.

Upgrade/Provisioning

าั¿½ Firmware upgrade via TFTP/HTTP/HTTPS, mass provisioning using TR-069 or AES encrypted XML configuration file

Power & amp; Green Energy Efficiency

ï¿⅓ Universal power adapter included: Input 100-240VAC 50-60Hz: Output: + 5vDC, 800mA

i;½ Intergrated Power-over-Ethernet (PoE) (802.3af, GXP1165 only)

تزاره Max power consumption 2.5w (universal power adapter) or 3w (PoE)

Physical



Grandstream GXP1165 IP Phone

آزا Unit dimension: 154mm (W) x 200mm (L) x 79mm D, handset onhook)

� Unit Weight: 0.6kg� Package Weight: 1.03KG

Temperature & amp; Humidity

2⁄ئ;ï

Operating 32 - 104 ° F / 0 -40 ° C, 10-90% (non-condensing); Storage: 14 - 140

° F.-10-60 ° C

Please Enquire