

Dinstar DWG2000C-4GSM VoIP Gateway



Product Name: Dinstar DWG2000C-4GSM VoIP Gateway

Manufacturer: -

Model Number: DWG2000C-4G

Please Note: The Dinstar DWG2000C-4GSM has been discontinued. For an alternative, we highly recommend the Dinstar DWG2000E 4-port GSM VoIP Gateway.

Dinstar DWG2000C-4GSM VoIP Gateway

The Dinstar DWG2000C-4G is fully functioning VoIP gateway based on IP and GSM network. The Dinstar DWG2000C-4G provides a flexible network configuration, powerful features, and good voice quality. It works for carrier grade, enterprise, SOHO, residential users for cost-effective solution. It's an easy to use cost-effective gateway for call termination (VoIP to GSM) and origination (GSM to VoIP). It is fully compatible with leading softswitch and SIP server.

Dinstar DWG2000C-4GSM VoIP Gateway Features

- PLC: Packet loss concealment
- VAD: Voice activity detection
- CNG: Comfort Noise Generation
- Local/Remote SIM card work mode
- Adjustable gain of port
- DTMF adjustment
- Balance alarm
- Lock/unlock SIM/UID
- Mobile number display rejection
- Sending/receiving SMS
- Customize IVR Recording
- White and black list
- One number access
- Open API for SMS, support USSD
- Echo Cancellation (with ITU-T G.168/165 standard)
- Automatic negotiate network
- Hotline
- BCCH

Technical Specification

Dimensions

• L = 255, W = 220, H = 30

Weight

• 1.4kg

Operation temperature(unit:°C)

• 0~40 °C

Storage temperature(unit:°C)

Dinstar DWG2000C-4GSM VoIP Gateway

ĩċ½
-20~80 ℃

Operation humidity

ĩċ½ 5%～90%

GSM SIM ports

ĩċ½ 4 GSM channels

Power supply

ĩċ½ 12VDC,4A

Power Consumption

ĩċ½ 25W

Network interface

ĩċ½ 10/100 Base-Tx, RJ45

Number of LAN ports

ĩċ½
1

Number of console

ĩċ½ 1

Please Enquire