

## CyberData VoIP V3 Indoor Intercom (011211)



Product Name: CyberData VoIP V3 Indoor Intercom (011211)

Manufacturer: CyberData

Model Number: 011211

CyberData VoIP V3 Indoor Intercom (011211)

The CyberData VoIP V3 Indoor Intercom (011211) is perfect for settings requiring two-way communication and secure access. The powerful processor allows for faster capabilities.

Key Features

- Simultaneous SIP and multicast
- Night Ringer function
- Dual speed 10/100 Mbps
- POE 802.3af
- SRST Support
- Network firmware upgradeable
- Network volume adjustable
- Network microphone sensitivity adjust
- Power-over-ethernet enabled
- Tamper sensor
- Dry contact relay

One of many within our line of Power-over-Ethernet (PoE 802.3af) intercoms, the v3 Indoor Intercom has been utilized within nursing care and assisted living facilities, schools and universities, daycare facilities, apartment complexes and more, delivering a versatile, cost-efficient alternative to old analog intercoms.

CyberData VoIP V3 Indoor Intercom (011211) Typical Install

CyberData VoIP V3 Indoor Intercom (011211) Technical Specifications

VoIP Intercom

- Protocol SIP RFC 3261 Compatible
- Ethernet I/F 10/100 Mbps
- Power Input PoE 802.3af or +5V at 1A
- Operating Temperature -30 to 55C (-22 to 131F)
- Payload Types G711 A-Law and u-Law
- Regulatory Compliance FCC Class A, UL 60950
- Dimension 5" x 5" x 2.5" (H x W x D)
- Warranty 2 Year Limited
- Part Number \*011211, RAL 9003, Signal White\*This number replaces the 011111 number.

Features

- PoE 802.3af enabled (Powered-over-Ethernet)
- SIP compliant
- Adaptive full-duplex voice operation
- Network web management
- Network adjustable speaker volume and microphone sensitivity
- Network downloadable firmware
- Concurrent SIP and multicast paging
- Dry relay contact for auxiliary control
- Peer-to-peer capable
- Door closure and tamper alert signal
- New Feature: Now supports SRST (Survivable
- Remote Site Telephony) in a Cisco environment.

CyberData VoIP V3 Indoor Intercom (011211)

**Price: £532.20**

---