

Alphatech Farfisa IP Bell 01C with 1 push button and camera VoIP SIP video Door entry System 220201



Product Name: Alphatech Farfisa IP Bell 01C with 1 push button and camera, VoIP SIP video Door entry

System 220201

Manufacturer: Alphatech Model Number: 220201

Alphatech Farfisa IP Bell 01C with 1 push button and camera, VoIP SIP video Door entry System - 220201

The Alphatech Farfisa IP Bell 01C with 1 push button and a camera, VoIP SIP video 220201 has an elegant design and robust IP audio video door station with slim and compact shape. Surface mounted, therefore extremely easy to install. Please Note: The main image shows the Features of Alphatech Farfisa IP Bell 01C with 1 push button and a camera, VoIP SIP video 220201

- า๊¿½ Buttons dial an extension or group when pressed
- រ៉េ¿½ Options for single/double buttoned which call different numbers/groups
- � One Backlit buttons
- าั¿½ Two internal SPDT relays for controlling a door opener or light etc.
- ī¿½ Relays controlled individually by DTMF tonesSIP Protocol

Usage scenarios
They can be deployed as:

- រ៉េ¿½ Office door phone with on-site or hosted IP-PBX, full access control
- ï¿⅓ Remote site entry over Internet
- آذِ1/2 Apartment/flat intercom with door access control

Name holders are back lit in original blue colour for easy identification even in poor lighting conditions. The front plate is made in anodised extruded alluminium. The IP Bell can be registered as an extension to any SIP based phone system. Callers at your door can talk to you whether you are on site or not. The camera option shows real-time video on either a computer or a SIP video telephone. To avoid wiring, the IP Bell can interface with a WiFi.The Alphatech Farfisa IP Bell 01C with 1 push button and a camera, VoIP SIP video 220201 consists of a camera door phone unit designed to sit on the outside of your premises plus 1 button. The Alphatech Farfisa IP Bell 01C with 1 push button and a camera, VoIP SIP video 220201 is slimline with a depth of just 30mm. Alphatech Farfisa IP Bell 01C with 1 push button and a camera, VoIP SIP video 220201 Technical Specifications

Compatible IP phone systems:

� 3CX

ï¿⅓ Aastra NeXspan

ï¿1/2 Alcatel OmniPCX

ï¿⅓ Asterisk

Avaya

ï¿1/2 Cisco CallManager v8.x

آزٰ½ Gigaset pro

ï¿⅓ Grandstream

ï¿⅓ IP Cortex

Karel IPv50

ï¿⅓ Mitel

� Nortel





Alphatech Farfisa IP Bell 01C with 1 push button and camera, VoIP SIP video Door entry System 220201

- � Panasonic
- � Quadro Epygi
- تز½ SARK
- ï¿⅓ Snom ONE
- ï¿⅓ SWYX
- าั¿½ Tested with Snom, Grandstream, Yealink, Polycom IP phones
- � Tested with 3CX softphones supporting Windows, Android and iOS

Power supply

- าั¿½ 12VDC ± 2V , 10-12VAC ± 2V
- ï¿1/2 Max. consumption: 300mA at 12VDC
- آزار Max. voltage of switch contact: 48V at I < 1A
- تزر Max. current of switch contact: 2A at U &It; 30 V
- ï¿1/2 802.3af Power-over-Ethernet

Working temperature

ï¿1/2 -20°C ÷ +50°C

Dimensions

� (HxWxD): 208x99x30mm

Body material

ï¿1/2 anodized aluminum and ABS plastic

VoIP and management

- آزا Session Initiation Protocol (SIP RFC3261)
- � Registers to a SIP Registrar/SIP PBX
- � Echo Cancellation
- ï¿⅓ Symmetric RTP
- � Codecs Audio: G711u, G.711a, G726, GSM
- ï¿1/2 Codecs Video: H.263 / H.264
- آزٰ Protocols: IP, TCP, UDP, HTTP, TELNET, SIP, RTP
- ї¿½ Interface : LAN 10/100 Base-Tx, RJ45
- � Resolution support: 640x480, 352x288, 320x240, 176x144, 160x120
- ï¿1/2 Frame rate: 1 to 7 pfs on H.263, 1 to 5 fps on H.264
- īస్ట్ Adjustable brightness, contrast, colour, hue and gamma from web GUI
- آزا Video access in VoIP call (RTP) or sequential JPEG from web GUI
- īస్ట్ High intensity white LEDs for picture lighting during dark hours with internal light sensor
- 17:1/2 HTTP web interface with password protection
- ï¿1/2 Video viewer in web GUI
- آذِيً Extract log files from web GUI (SIP trace, call log, general log)
- ï¿1/2 Telnet command line interface
- ï¿1/2 Log to syslog server
- � Editable web GUI language file

Price: £346.55