CyberData SIP Paging Adapter (011233)



Product Name: CyberData SIP Paging Adapter (011233)
Manufacturer: CyberData
Model Number: 011233

CyberData SIP Paging Adapter 011233
The CyberData SIP Paging Adapter is a VoIP endpoint that interfaces analog paging systems with SIP and Multicast-based audio sources. The SPA (SIP Paging Adapter) can be configured to support two separate SIP extensions.
CyberData SIP Paging Adapter Key Features

ï¿½ Two SIP extensions
ï¿½ Page to Polycom phones
ï¿½ Voice prompt Pass code
ï¿½ User uploadable Page messages
ï¿½ HTTPS status and command interface
ï¿½ 10 channel prioritized Multicast ports
ï¿½ HTTPS Web Interface and setup
ï¿½ Built-in diagnostics

SIP extension one passes audio through to the analog output spoken from the caller’s handset. When called, SIP extension two plays a bell audio that can be used as a night ringer when configured in a night ring group. The SPA supports up to 9 user-loadable messages that can be played by a DTMF command. The SPA supports a line-In input for playing music on hold. During a page or a stored audio file message, this input is muted with its output restored once the page has stopped.
Messages can be played either:

ï¿½ SIP to Analog
ï¿½ Line-in to Analog
ï¿½ Multicast to analog
ï¿½ HTTPS command interface

CyberData SIP Paging Adapter 011233 Additional Features

ï¿½ 10k Ohm input for MOH
ï¿½ 600 Ohm Balanced audio out
ï¿½ Unbalanced Line-Out
ï¿½ Remote amp fault sensor
ï¿½ DTMF and programmatic controlled Relay
ï¿½ Delayed page support
ï¿½ DTMF pass-through
ï¿½ Cisco SRST
ï¿½ 10/100 802.3af PoE

Technical Specifications of CyberData SIP Paging Adapter 011233
General

ï¿½ Protocol: SIP RFC 3261 Compatible
ï¿½ Ethernet I/F: 10/100 Mbps
ï¿½ Power Input: PoE 802.3af or 48VDC
ï¿½ Operating Temperature: -30 to 55 C (-22 to 131 F)

CyberData SIP Paging Adapter (011233)

ï¿½ Payload Types: G711
ï¿½ Regulatory Compliance: FCC Class A, UL 60950
ï¿½ Page Port Output: Balanced 600 Ohm 10VPP
ï¿½ Line In:Input Signal Amplitudes: 2.0 VPP maximumInput Impedance: 10k Ohm
ï¿½ Line Out:Output Signal Amplitudes: 2.0 VPP maximumOutput Level: +2dBm nominalTotal Harmonic Distortion: 0.5% maximumOutput Impedance: 10k Ohm
ï¿½ Dimensions: 6.11"L x 4.05"W x 1.15"H
ï¿½ Warranty: 2 years limited
ï¿½ Boxed Weight: 1.8 lbs.

Price: £439.40